

### B13 Decorative CFLi Lamps

Ordering Code	Barcode	Watts	Volts	Base	Approx Initial Lumens	CRI	CT° K	MOL in/mm	mg Hg	Life	Approvals
<b>SP5B13/E26/27K</b>	06452	5		E26	220	80	2700	4.449/113	1.6	10,000	
<b>SP5B13/E26/41K</b>	06453	5		E26	220	80	4100	4.449/113	1.6	10,000	

### G25 Decorative CFLi Lamps

Ordering Code	Barcode	Watts	Volts	Base	Approx Initial Lumens	CRI	CT° K	MOL in/mm	mg Hg	Life	Approvals
<b>SP9G25/27K</b>	06550	9		E26	500	80	2700	4.331/110	1.6	10,000	
<b>SP9G25/41K</b>	06551	9		E26	500	80	4100	4.331/110	1.6	10,000	
<b>SP15G25/27K</b>	07870	15	120	E26	820	80	2700	4.724/120	1.6	10,000	UL/CSA, Energy Star, TCLP Compliant
<b>SP15G25/27K-GU24</b>	07734	15	120	GU24	740	>80	2700	4.45/113	1.6	10,000	UL/CSA, Energy Star, TCLP Compliant
<b>SP15G25/41K</b>	07871	15	120	E26	820	80	4100	4.724/120	1.6	10,000	UL/CSA, TCLP Compliant

### High Watt CFLi Lamps

Ordering Code	Barcode	Watts	Volts	Base	Approx Initial Lumens	CRI	CT° K	MOL in/mm	mg Hg	Life	Approvals
<b>SP65/41/MED</b>	05293	65	120	E26	4300	>80	4100	9.45/240	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP65/50/MED</b>	06659	65	120	E26	4000	>80	5000	9.45/240	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP85/41/MED</b>	81183	85	120	E26	5700	>80	4100	9.96/253	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP85/50/MED</b>	81181	85	120	E26	5350	>80	5000	9.96/253	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP105/41/MED</b>	81184	105	120	E26	7000	>80	4100	10.75/273	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP105/41/MOG</b>	81185	105	120	E39	7000	>80	4100	11.26/286	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP105/41/MOG-277V</b>	04412	105	277	E39	7000	>80	4100	11.26/286	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP105/50/MED</b>	81180	105	120	E26	6600	>80	5000	10.75/273	4.8	10,000	UL/CSA, TCLP Compliant
<b>SP180/41/MOG</b>	07822	180	120	E39	11,100	80	4100	14.3/364	9.2	10,000	UL/CSA, TCLP Compliant
<b>SP180/50/MOG</b>	07823	180	120	E39	10,400	80	5000	14.3/364	9.2	10,000	UL/CSA, TCLP Compliant

### PAR CFLi Lamps

Ordering Code	Barcode	Watts	Volts	Base	Approx Initial Lumens	CRI	CT° K	MOL in/mm	mg Hg	Life	Approvals
<b>PAR20/9/30K</b>	06281	9	120	E26	280	>80	3000	3.82/97	1.35	8,000	UL/CSA, Energy Star, TCLP Compliant
<b>PAR20/9/35K</b>	01519	9	120	E26	272	>80	3500	3.82/97	1.35	8,000	UL/CSA, TCLP Compliant
<b>PAR20/9/41K</b>	06282	9	120	E26	270	>80	4100	3.82/97	1.35	8,000	UL/CSA, Energy Star, TCLP Compliant
<b>PAR20/9/50K</b>	01521	9	120	E26	258	>80	5000	3.82/97	1.35	8,000	UL/CSA, TCLP Compliant
<b>PAR30LN/15/30K</b>	06279	15	120	E26	750	>80	3000	5.12/130	1.93	8,000	UL/CSA, TCLP Compliant
<b>PAR30LN/15/35K</b>	01522	15	120	E26	728	>80	3500	5.12/130	1.93	8,000	UL/CSA, TCLP Compliant
<b>PAR30LN/15/41K</b>	06280	15	120	E26	725	>80	4100	5.12/130	1.93	8,000	UL/CSA, Energy Star, TCLP Compliant
<b>PAR30LN/15/50K</b>	01523	15	120	E26	745	>80	5000	5.12/130	1.93	8,000	UL/CSA, Energy Star, TCLP Compliant
<b>PAR38/23/27K</b>	01046	23	120	E26	1250	>80	2700	5.51/140	2.31	8,000	UL/CSA, TCLP Compliant
<b>PAR38/23/30</b>	06277	23	120	E26	1200	>80	3000	5.51/140	2.31	8,000	UL/CSA, Energy Star, TCLP Compliant
<b>PAR38/23/30K</b>	06277	23	120	E26	1200	>80	3000	5.51/140	2.5	8,000	UL/CSA, TCLP Compliant

>>Continued on page 32

