

Motorcycle and Snowmobile Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
A-3603-BP	48009	25/25	12/12	PX15d	C-2V/C-2V	1.85/47.0	0.79/20.1	100/100
A-3625	48010	25/25	6.5/6.5	PX15d	C-2V/C-2V	1.85/47.0	0.79/20.1	150/150
A-3625-BP	48011	25/25	6.5/6.5	PX15d	C-2V/C-2V	1.85/47.0	0.79/20.1	150/150
HM201	00385	30/30	12.8/12.8	PX15d25-1	C-6/C-6	1.63/41.3	0.40/10.2	300/320
A-7025-BP	48027	35/25	13/13	P15d-3	C-6/C-2V	2.20/56.0	1.38/35.0	100/100
6235B	48056	35/35	12.8/12.8	BA20d	C-8/C-2R	2.60/66.0	1.42/36.0	100/100
6235B-BP	48057	35/35	12.8/12.8	BA20d	C-8/C-2R	2.60/66.0	1.42/36.0	100/100
6235J	48038	35/35	12.8/12.8	P15d-3	C-6/C-6	2.25/57.2	1.25/32.0	100/100
6235J-BP	57033	35/35	12.8/12.8	P15d-3	C-6/C-6	2.25/57.2	1.25/32.0	100/100
6235Y	48028	35/35	12.8/12.8	P15d30	C-6/C-6	2.30/58.4	1.38/35.0	100/100
6235Y-BP	57032	35/35	12.8/12.8	P15d30	C-6/C-6	2.30/58.4	1.38/35.0	100/100
A-5659	48024	35/35	6.5/6.5	P15d30	C-6/C-2V	2.20/56.0	1.26/32.0	100/100
A-5659-BP	48025	35/35	6.5/6.5	P15d30	C-6/C-2V	2.20/56.0	1.26/32.0	100/100
4745-BP	57044	45/45	12.8/12.8	P43t38	C-8/C-8	3.63/92.1	0.67/17.0	120/250
6245B	48058	45/45	12.8/12.8	BA20d	C-8/C-2R	2.60/66.0	1.42/36.0	100/100
6245B-BP	48059	45/45	12.8/12.8	BA20d	C-8/C-2R	2.60/66.0	1.42/36.0	100/100
6245BA	48062	45/45	12.8/12.8	P45t41	C-8/C-2R	3.00/76.2	1.61/41.0	100/100
6245BA-BP	48063	45/45	12.8/12.8	P45t41	C-8/C-2R	3.00/76.2	1.61/41.0	100/100
6245J-BP	48041	45/45	12.8/12.8	P15d-3	C-6/C-2V	2.25/57.2	1.25/32.0	100/100
6245Y-BP	48031	45/45	12.8/12.8	P15d30	C-6/C-6	2.30/58.4	1.38/35.0	100/100
6255BAH-BP	48067	60/55	12.8/12.8	P45t41	C-8/C-8	3.62/92.0	0.65/16.5	150/300
6260HD-BP	48097	60/55	12/12	P43t38	C-8/C-8	3.62/92.0	0.65/16.5	150/300
6361-BP	57027	60/55	12.8/12.8	P45t41	C-8/C-8	3.62/92.0	0.65/16.5	150/300
6260B-BP	48061	60/60	12.8/12.8	BA20d	C-8/C-2R	2.60/66.0	1.42/36.0	75
6260BA	48064	60/60	12.8/12.8	P45t41	C-8/C-2R	3.00/76.2	1.61/41.0	75/75
6260BA-BP	48065	60/60	12.8/12.8	P45t41	C-8/C-2R	3.00/76.2	1.61/41.0	75/75
6260J	48042	60/60	12.8/12.8	P15d-3	C-6/C-2V	2.25/57.2	1.25/32.0	75/75
6260J-BP	48043	60/60	12.8/12.8	P15d-3	C-6/C-2V	2.25/57.2	1.25/32.0	75/75
6260S	48036	60/60	12.8/12.8	P36t	C-6/C-6	3.00/76.2	1.42/36.0	75/75
6260S-BP	48037	60/60	12.8/12.8	P36t	C-6/C-6	3.00/76.2	1.42/36.0	75/75
6260SA-BP	48035	60/60	12.8/12.8	P43t38	C-8/C-2R	3.00/76.2	1.42/36.0	75/75
6255BAHP-BP	48069	100/55	12.8/12.8	P45t41	C-8/C-8	3.62/92.0	0.65/16.5	100/200
6260HP-BP	48073	100/55	12/12	P43t38	C-8/C-8	3.62/92.0	0.65/16.5	100/200
6263-BP	48096	100/55	12/12	P43t38	C-8/C-8	3.62/92.0	0.65/16.5	100/200
6265-BP	48095	100/80	12/12	P43t38	C-8/C-8	3.62/92.0	0.65/16.5	100/200
6365	48093	100/80	12.8/12.8	P45t41	C-8/C-8	3.63/92.1	0.67/17.0	100/200
6365-BP	48094	100/80	12.8/12.8	P45t41	C-8/C-8	3.63/92.1	0.67/17.0	100/200

Halogen Sealed Beam Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
H7550	91074	8	6	2 MP	C-6	2.75/70	4.5/114.3	50
36PAR36/CAP/WFL32	81166	36	12	2 MP	C-6	2.36/60	4.5/114.3	4,000
H7600	91072	37.5	12.8	2 MP	C-6	2.75/70	4.5/114.3	300
H7616	91073	37.5	12.8	2 MP	C-6	2.75/70	4.5/114.3	300
H9415	91099	37.5	12.8	2 Rt Angle Lugs	C-6	3.0/76		200 at 14V

>>Continued on page 70



HM201



6235B



6260BA



H9415