

9000 Series Halogen Forward Lighting

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
9006XS	49416	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
9006XS-BP	49417	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,000
9006XSLL	00237	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,500
9006XSLL-BP	05356	55	12.8	P22d	C-8	1005	2.61/66.29	0.42/10.7	1,500
9155	06429	55	12.8	P20d/55a	C-8	940	3.17/80.5	0.5/12.4	1,200
9012LL	00732	60	12.8	PX22d	C-8	1695	3.09/78.5	0.43/11.0	1000 at 14V
9005	41052	65	12.8	P20d	C-8	1695	3.09/78.0	0.42/10.7	320
9005-BP	41053	65	12.8	P20d	C-8	1695	3.09/78.0	0.42/10.7	320
9005XS	49413	65	12.8	P20d	C-8	1695	2.59/65.9	0.42/10.7	320
9005XS-BP	49414	65	12.8	P20d	C-8	1695	2.59/65.9	0.42/10.7	320
9005XSLL	00236	65	12.8	P20d	C-8	1695	2.59/65.9	0.42/10.7	320
9011	00711	65	12.8	PX20d	C-8	2300	3.09/78.5	0.5/12.5	150 at 14V
9006HW	43564	80	12.8	P22d	C-8	1345	3.09/78.0	0.42/10.7	1,000
9003	42268	60/55	12.8/12.8	P43t38	C-8/C-8	1545/955	3.62/92.0	0.65/16.5	250/800
9003-BP	42064	60/55	12.8/12.8	P43t38	C-8/C-8	1545/955	3.62/92.0	0.65/16.5	250/800
9004	41008	65/45	12.8/12.8	P29t	C-6/C-6	1195/690	4.17/106	1.33/33.8	250/500
9004-BP	41009	65/45	12.8/12.8	P29t	C-6/C-6	1195/690	4.17/106	1.33/33.8	250/500
9004LL	41063	65/45	12.8/12.8	P29t	C-6/C-6	1195/690	4.17/106	1.33/33.8	250/500
9004LL-BP	41062	65/45	12.8/12.8	P29t	C-6/C-6	1195/690	4.17/106	1.33/33.8	250/500
9007	42426	65/55	12.8/12.8	Px29t	C-8/C-8	1345/1105	4.17/106	1.33/33.8	250/500
9007-BP	42124	65/55	12.8/12.8	Px29t	C-8/C-8	1345/1105	4.17/106	1.33/33.8	250/500
9007LL	44176	65/55	12.8/12.8	Px29t	C-8/C-8	1345/1105	4.17/106	1.33/33.8	250/1500
9007LL-BP	44178	65/55	12.8/12.8	Px29t	C-8/C-8	1345/1105	4.17/106	1.33/33.8	250/1500
9008	49865	65/55	12.8/12.8	P26.4t	C-8/C-8	1510/1005	3.68/93.6	0.63/16.0	250/1500
9008-BP	49867	65/55	12.8/12.8	P26.4t	C-8/C-8	1510/1005	3.68/93.6	0.63/16.0	250/1500
9004HW	43504	100/80	12.8/12.8	P29t	C-6/C-6	1545/1255	4.17/106	1.33/33.8	250/500
9007HW	43517	100/80	12.8/12.8	Px29t	C-8/C-8	1695/1445	4.17/106	1.33/33.8	250/500

800 Series Halogen Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
882	42100	4.5	12.8	B10d	C-6	48	1.18/30.0	0.72/18.3	2,000
882-BP	42096	4.5	12.8	B10d	C-6	48	1.18/30.0	0.72/18.3	2,000
891	42116	8	12.8	G4	C-6	145	1.20/30.5	0.32/8.1	800
891-BP	42114	8	12.8	G4	C-6	145	1.20/30.5	0.32/8.1	800
880	42450	27	12.8	PG13	C-6	565	2.68/68.1	0.42/10.7	500
880-BP	42088	27	12.8	PG13	C-6	565	2.68/68.1	0.42/10.7	500
880SW-BP	49435	27	12.8	PG13	C-6	565	2.68/68.1	0.42/10.7	500
881	42452	27	12.8	PGJ13	C-6	565	2.68/68.1	0.42/10.7	500
881-BP	42094	27	12.8	PGJ13	C-6	565	2.68/68.1	0.42/10.7	500
881SW-BP	49436	27	12.8	PGJ13	C-6	565	2.68/68.1	0.42/10.7	500
889	42460	27	12.8	PGJ13	C-6	565	2.68/68.1	0.42/10.7	500
889-BP	42106	27	12.8	PGJ13	C-6	565	2.68/68.1	0.42/10.7	500
890	42462	27	12.8	PG13	C-6	565	2.68/68.1	0.42/10.7	500
890-BP	42110	27	12.8	PG13	C-6	565	2.68/68.1	0.42/10.7	500
862	00043	37.5	12.8	PGJ13	C-6	755	2.68/68.1	0.42/10.7	2,000

>>Continued on page 66

