

G6.35 Base 2-pin Halogen Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
JC12V20WH20	15013	20	12	G6.35	C-6	350	1.73/44.0	0.46/11.5	2,000
JC12V30WH20	15015	30	12	G6.35	C-6	560	1.73/44.0	0.46/11.5	2,000
JC12V35WH20	15017	35	12	G6.35	C-6	600	1.73/44.0	0.46/11.5	2,000
JC12V50WH20	15019	50	12	G6.35	C-8	950	1.73/44.0	0.46/11.5	2,000
JC12V75WH20	15021	75	12	G6.35	C-6	1600	1.73/44.0	0.46/11.5	2,000
JC12V100WH20	15023	100	12	G6.35	C-6	2000	1.73/44.0	0.51/13.0	1,200

Bi-pin Line Voltage Halogen Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
JCD130V20WG6.35	00307	20	130	G6.35	CC-6V	130	1.44/36.5	0.52/13	1,500
JCD130V20WG8	00314	20	130	G8	CC-6V	130	1.44/36.5	0.52/13	1,500
JCD130V25WG6.35	00308	25	130	G6.35	CC-6V	170	1.44/36.5	0.52/13	1,500
JCD130V25WG8	00315	25	130	G8	CC-6V	170	1.44/36.5	0.52/13	1,500
JCD130V25WG9	00321	25	130	G9	4-Style	180	1.81/46	0.52/13	2,000
JCD130V25WG9/F	00326	25	130	G9	4-Style	170	1.81/46	0.52/13	2,000
JCD130V35WG6.35	00309	35	130	G6.35	CC-6V	380	1.77/45	0.52/13	2,000
JCD130V35WG8	00316	35	130	G8	CC-6V	380	1.77/45	0.52/13	2,000
JCD130V40WG9	00322	40	130	G9	4-Style	400	1.81/46	0.52/13	2,000
JCD130V40WG9/F	00327	40	130	G9	4-Style	380	1.81/46	0.52/13	2,000
JCD130V50WG6.35	00311	50	130	G6.35	CC-2V	600	1.77/45	0.52/13	2,000
JCD130V50WG8	00317	50	130	G8	CC-2V	600	1.77/45	0.52/13	2,000
JCD130V50WG9	00323	50	130	G9	4-Style	550	1.81/46	0.52/13	2,000
JCD130V50WG9/F	00328	50	130	G9	4-Style	500	1.81/46	0.52/13	2,000
JCD130V60WG9	00324	60	130	G9	4-Style	720	1.93/49	0.52/13	1,500
JCD130V60WG9/F	00329	60	130	G9	4-Style	680	1.93/49	0.52/13	1,500
JCD130V75WG6.35	00312	75	130	G6.35	CC-7A	930	1.77/45	0.52/13	2,000
JCD130V75WG8	00318	75	130	G8	CC-7A	930	1.77/45	0.52/13	2,000
JCD130V75WG9	00325	75	130	G9	4-Style	900	1.93/49	0.52/13	1,500
JCD130V75WG9/F	00331	75	130	G9	4-Style	850	1.93/49	0.52/13	1,500
JCD130V100WG8	00319	100	130	G8	CC-7A	1450	1.97/50	0.53/13.5	1,500

Halogen Heat Lamps

Ordering Code	Barcode	Watts	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
17002	17002	375	115-125	6 in Leads	C-8	8.82/224.0	0.40/10.0	5,000
17004	17004	375	115-125	R7s	C-8	8.70/221.0	0.40/10.0	5,000
17006	17006	500	115-125	6 in Leads	C-8	8.82/224.0	0.40/10.0	5,000
17008	17008	500	115-125	6 in Leads	C-8	8.82/224.0	0.40/10.0	5,000
17010	17010	500	115-125	R7s	C-8	8.70/221.0	0.40/10.0	5,000
17012	17012	1000	200-220	6 in Leads	C-8	13.78/350.0	0.40/10.0	5,000
17014	17014	1000	230-250	6 in Leads	C-8	13.78/350.0	0.40/10.0	5,000
17016	17016	1000	230-250	6 in Leads	C-8	11.89/302.0	0.40/10.0	5,000
17018	17018	1000	230-250	6 in Leads	C-8	13.78/350.0	0.40/10.0	5,000
17022	17022	1200	144	6 in Leads	C-8	8.82/224.0	0.40/10.0	5,000
17024	17024	1600	200-220	6 in Leads	C-8	19.80/503.0	0.40/10.0	5,000
17026	17026	1600	230-250	6 in Leads	C-8	19.80/503.0	0.40/10.0	5,000
17028	17028	1600	277	6 in Leads	C-8	19.80/503.0	0.40/10.0	5,000
17030	17030	1600	230-250	6 in Leads	C-8	19.80/503.0	0.40/10.0	5,000
17032	17032	1600	200-220	R7s	C-8	19.63/498.5	0.40/10.0	5,000
17034	17034	1600	230-250	R7s	C-8	19.63/498.5	0.40/10.0	5,000
17040	17040	2000	230-250	6 in Leads	C-8	13.78/350.0	0.40/10.0	5,000

>>Continued on page 57

