

Rough Service Incandescent Lamps

Ordering Code	Barcode	Watts	Volts	Shape	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
100A/RS/TF	15810	100	130	A-19	E26	C-9	1000	4.44/112.8	2.38/60.3	5,000
150A/RS	00008	150	130	A-21	E26	C-9	1650	4.96/126	2.63/66.7	5,000
150A/RS/TF	01863	150	130	A-21	E26	C-9	1650	4.96/126	2.63/66.7	5,000

C Shaped Incandescent Lamps

Ordering Code	Barcode	Watts	Volts	Shape	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
4C7/120V	40353	4	120	C-7	E12	C-7A	20	2.30/58.4	0.88/22.3	3,000
4C7/130V	40351	4	130	C-7	E12	C-7A	15	2.30/58.4	0.88/22.3	3,000
7C7/120V	40874	7	120	C-7	E12	C-7A	37	2.30/58.4	0.88/22.3	3,000
7C7/130V	40875	7	130	C-7	E12	C-7A	35	2.30/58.4	0.88/22.3	3,000
7C7/130V-W	44318	7	130	C-7	E12	C-7A	n/a	2.30/58.4	0.88/22.3	3,000
7C9-120V-INT	01709	7	120	C-9	E17	C-5A	45	3.9/99	1.15/29.2	3,000
10C7/120V	40073	10	120	C-7	E12	C-7A	64	2.30/58.4	0.88/22.3	5000+
10C7DC/120V	40154	10	120	C-7	BA15d	C-7A	64	2.13/54.1	0.88/22.3	5000+

R & BR Incandescent Lamps

Ordering Code	Barcode	Watts	Volts	Shape	Base	Filament	Lumens	MOL in/mm	Life
30R20/FL-120V	49791	30	120	R-20	E26	CC-6	180	3.94/100	2,000
30R20/FL-130V	49792	30	130	R-20	E26	CC-6	245	3.94/100	5000 Hrs at 120v
45BR30/FL-120V	49797	45	120	BR-30	E26	CC-6	390	5.38/136.7	2,000
45R20/FL-120V	05986	45	120	R-20	E26	CC-6	360	3.94/100	2,000
45R20/FL-130V	05987	45	130	R-20	E26	CC-6	340	3.94/100	5000 Hrs at 120v
65BR30/FL-120V	49798	65	120	BR-30	E26	CC-6	620	5.38/136.7	2,000
65BR30/FL-130V	49799	65	130	BR-30	E26	CC-6	620	5.38/136.7	5000 Hrs at 120v
65BR30/SP-120V	49811	65	120	BR-30	E26	CC-6	620	5.38/136.7	2,000
65BR30/SP-130V	49800	65	130	BR-30	E26	CC-6	620	5.38/136.7	5000 Hrs at 120v
65BR40/FL-120V	49801	65	120	BR-40	E26	CC-6	620	6.56/166.6	2,000
65BR40/FL-130V	49802	65	130	BR-40	E26	CC-6	620	6.56/166.6	5000 Hrs at 120v

S Shaped Incandescent Lamps

Ordering Code	Barcode	Watts	Volts	Shape	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
3S6/5-120V	40552	3	120	S-6	E12	C-7A	11.31	1.88/47.8	0.75/19.1	1,500
3S6/5-130V	40554	3	130	S-6	E12	C-7A	11.31	1.88/47.8	0.75/19.1	1,500
3S6/5DC-120V	40556	3	120	S-6	BA15d	C-7A	11.31	1.82/46.2	0.75/19.1	3,000
6S6/120V	40786	6	120	S-6	E12	C-7A	39	1.88/47.8	0.75/19.1	1,500
6S6/12V	40784	6	12	S-6	E12	C-6	48	1.88/47.8	0.75/19.1	1,500
6S6/130V	40788	6	130	S-6	E12	C-7A	38	1.88/47.8	0.75/19.1	1,500
6S6/145V	40789	6	145	S-6	E12	C-7A	17.60	1.88/47.8	0.75/19.1	1,500
6S6/155V	40790	6	155	S-6	E12	C-7A	33	1.88/47.8	0.75/19.1	1,500
6S6/18V	49717	6	18	S-6	E12	C-6	50	1.88/47.8	0.75/19.1	1,500
6S6/230V	40791	6	230	S-6	E12	C-7A	11.31	1.88/47.8	0.75/19.1	1,500
6S6/24V	40792	6	24	S-6	E12	C-6	53	1.88/47.8	0.75/19.1	1,500

>>Continued on page 60



C Shaped



R20



R30



R40



S Shaped