

S Shaped Incandescent Lamps

Ordering Code	Barcode	Watts	Volts	Shape	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
6S6/30V	40794	6	30	S-6	E12	C-6	52	1.88/47.8	0.75/19.1	1,500
6S6/48V	40796	6	48	S-6	E12	C-6	47	1.88/47.8	0.75/19.1	1,500
6S6/60V	40800	6	60	S-6	E12	C-7A	43	1.88/47.8	0.75/19.1	1,500
6S6/6V	40798	6	6	S-6	E12	C-6	54	1.88/47.8	0.75/19.1	1,500
6S6DC/120V	40804	6	120	S-6	BA15d	C-7A	39	1.82/46.2	0.75/19.1	1,500
6S6DC/12V	40802	6	12	S-6	BA15d	C-6	48	1.82/46.2	0.75/19.1	1,500
6S6DC/130V	40806	6	130	S-6	BA15d	C-7A	38	1.82/46.2	0.75/19.1	1,500
6S6DC/145V	40807	6	145	S-6	BA15d	C-7A	17.60	1.82/46.2	0.75/19.1	1,500
6S6DC/24V	40808	6	24	S-6	BA15d	C-6	53	1.82/46.2	0.75/19.1	1,500
6S6DC/30V	40810	6	30	S-6	BA15d	C-6	52	1.82/46.2	0.75/19.1	1,500
6S6DC/32V	40811	6	32	S-6	BA15d	C-6	50	1.82/46.2	0.75/19.1	1,500
6S6DC/48V	40812	6	48	S-6	BA15d	C-6	47	1.82/46.2	0.75/19.1	1,500
6S6DC/60V	40816	6	60	S-6	BA15d	C-7A	43	1.82/46.2	0.75/19.1	1,500
6S6DC/6V	40814	6	6	S-6	BA15d	C-6	54	1.82/46.2	0.75/19.1	1,500
10S6/120V	00020	10	120	S-6	E12	C-7A	60	1.88/47.8	0.75/19.1	1,500
10S6/230V	42446	10	230	S-6	E12	C-7A	60	1.88/47.8	0.75/19.1	1,500
10S6/250V	16013	10	250	S-6	E12	C-7A	60	1.88/47.8	0.75/19.1	1,500
10S6DC/250V	40149	10	250	S-6	BA15d	C-7A	60	1.82/46.2	0.75/19.1	1,500
40S11N	01268	40	130	S-11	E17	C-2V		2.45/62	1.42/36	3500 at 120V

T Shaped Incandescent Lamps

Ordering Code	Barcode	Watts	Volts	Shape	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
15T4C-130V	16017	15	130	T-4	E12	C-7A	90	1.97/50.0	0.54/39.1	1,500
15T6C-120V	81134	15	120	T-6	E12	C-7A	90	3.06/77.7	0.77/19.6	2,000
15T6C-130V	43000	15	130	T-6	E12	C-7A	90	3.06/77.7	0.77/19.6	2,000
15T6C-145V	43002	15	145	T-6	E12	C-7A	90	3.06/77.7	0.77/19.6	2000, (7500 @ 120V)
15T7C-130V	43006	15	130	T-7	E12	C-7A	90	2.25/57.2	0.89/22.6	1,500
15T7DC-130V	43008	15	130	T-7	BA15d	C-7A	90	2.25/57.2	0.89/22.6	1,500
15T7N-130V	43004	15	130	T-7	E17	C-7A	90	2.25/57.2	0.89/22.6	1,500
20T6-1/2DC-130V	43014	20	130	T-6 1/2	BA15d	C-8	180	5.56/141.2	0.83/21.1	3,000
20T6-1/2F-130V	43012	20	130	T-6 1/2	E17	C-8	170	5.5/139.7	0.83/21.1	3,000
20T6-1/2N-130V	43010	20	130	T-6 1/2	E17	C-8	180	5.5/139.7	0.83/21.1	3,000
20T6-1/2N-145V	44402	20	145	T-6 1/2	E17	C-8	170	5.5/139.7	0.83/21.1	3,000
20T6.5DC/F-130V	43016	20	130	T-6 1/2	BA15d	C-8	170	5.56/141.2	0.83/21.1	3,000
25T10-130V	43034	25	130	T-10	E26	C-5V	180	5.19/131.8	1.25/31.8	2,000
25T10/F-130V	43036	25	130	T-10	E26	C-8	200	5.19/131.8	1.25/31.8	1,500
25T10/IF-120	41522	25	120	T-10	E26	C-8		5.19/131.8	1.25/31.8	1,500
25T6-1/2DC-130V	43024	25	130	T-6 1/2	BA15d	C-8	210	5.5/139.7	0.83/21.1	3,000
25T6-1/2N-130V	43020	25	130	T-6 1/2	E17	C-8	210	5.5/139.7	0.83/21.1	3,000
25T6.5DC/F-130V	43026	25	130	T-6 1/2	BA15d	C-8	200	5.56/141.2	0.83/21.1	3,000
25T6.5N/F-130V	43022	25	130	T-6 1/2	E17	C-8	200	5.5/139.7	0.83/21.1	3,000
25T6C-120V	43018	25	120	T-6	E12	C-7A	190	3.06/77.7	0.77/19.6	2,000
25T8C-120V	43028	25	120	T-8	E12	C-7A	180	2.63/66.8	1.04/26.4	1,500
25T8DC-120V	49563	25	120	T-8	BA15d	C-7A	180	2.63/66.8	1.04/26.4	1,500

>>Continued on page 61



S Shaped



S Shaped