



SWING ARM TV WALL MOUNTS

THINSTALL™ SWING ARM FEATURES



ULTRA-LOW PROFILE

These sleek designs retract down to 1.5 to 1.8" (38 to 46 mm) to provide an ultra-thin profile to showcase any flat-screen display.



CENTERLESS™ SHIFT

Generous post-installation lateral shift up to 16" (406 mm) allows for perfect display positioning.



CABLE MANAGEMENT

Enclosed, tool-less cable covers and a wide open wall plate make it easy to route power and signal cables.



CENTRIS™ FINGERTIP TILT

Uses the center of gravity to balance the screen for up to 15 degrees of easy tilt capability.



HEIGHT ADJUST

Adjust the height of the entire configuration post installation up to 1" (25 mm).

TS525TU 37 - 58" EXTENDS 25" (635 mm)



This feature-rich swing arm fits most screens and has a large array of supporting accessories.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
125 lbs (56.7 kg)	20.7 x 29.5 x 1.5" (527 x 749 x 38 mm)	100 x 100 - 800 x 400 mm	25" (635 mm)	16" (406 mm)	-15°	1" (25 mm)



TS325TU 26 - 52" EXTENDS 25" (635 mm)



Very similar to the TS525TU but with a shorter wall plate and modified interface making it better suited for lighter displays.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
75 lbs (34 kg)	17.3 x 22.6 x 1.8" (439 x 574 x 46 mm)	100 x 100 - 600 x 400 mm	25" (635 mm)	16" (406 mm)	-15°	1" (25 mm)



TS318TU 26 - 52" EXTENDS 18" (457 mm)



This mount has the same features as the TS325TU with 18" (462 mm) extension.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
75 lbs (34 kg)	17.3 x 22.6 x 1.8" (439 x 574 x 46 mm)	100 x 100 - 600 x 400 mm	18" (457 mm)	16" (406 mm)	-15°	1" (25 mm)



TS318SU 26 - 52" EXTENDS 18" (457 mm)



This single stud version of the TS318 dual arm swing arm mount works well when lateral shift is not a necessity.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
75 lbs (34 kg)	13.5 x 22.6 x 1.8" (343 x 574 x 46 mm)	100 x 100 - 600 x 400 mm	18" (457 mm)	N/A	-15°	1" (25 mm)



TS218SU 26 - 47" EXTENDS 18" (457 mm)



This single stud swing arm works well in corners and with most medium flat panels. It also accommodates portrait and landscape orientations.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
75 lbs (34 kg)	14 x 13 x 1.5" (356 x 330 x 38 mm)	100 x 100 - 400 x 400 mm	18" (457 mm)	N/A	-12°	1" (25 mm)



TS118SU 10 - 32" EXTENDS 18" (457 mm)



Fits smaller patterns and screens than the TS218SU.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
35 lbs (15.9 kg)	11.6 x 13 x 1.5" (294 x 330 x 38 mm)	75 x 75 - 200 x 200 mm	18" (457 mm)	N/A	-12°	N/A



TS110SU 10 - 32" EXTENDS 9.85" (250 mm)



This basic swing arm wall mount provides single arm extension and swivel for smaller displays.

Weight Capacity	Dimensions (HxWxD)	Mounting Patterns (WxH)	Extension	Max. Lateral Shift	Tilt	Height Adjust
35 lbs (15.9 kg)	9.4 x 14 x 1.5" (239 x 356 x 38 mm)	75 x 75 - 200 x 200 mm	9.85" (250 mm)	N/A	-12°	N/A



THININSTALL™ SWING ARM ACCESSORIES



TA100	Dimensions (WxD)	Weight Capacity	Compatibility
Component Shelf	18 x 12" (457 x 305 mm)	10 lbs (4.5 kg)	TS525TU, TS325TU, TS318TU, TS318SU



TA200/250		Compatibility
Video Conference Camera Shelves - Above		TS525TU, TS325TU, TS318TU, TS318SU
Model	Dimensions (WxD)	Weight Capacity
TA200	8 x 7.3" (203 x 184 mm)	10 lbs (4.5 kg)
TA250	12 x 7.3" (305 x 184 mm)	10 lbs (4.5 kg)



TA300	Weight Capacity	Compatibility
Left/Right Speaker Adapter	10 lbs (4.5 kg)	TS525TU, TS325TU, TS318TU, TS318SU



TA350	Weight Capacity	Compatibility
Center Channel Speaker Adapter	10 lbs (4.5 kg)	TS525TU, TS325TU, TS318TU, TS318SU



TA410	Compatibility
Portrait Adapter	TS525TU, TS325TU, TS318TU, TS318SU



TA500	Dimensions (HxWxD)	Compatibility
Large In-Wall Swing Arm Accessory	21.75 x 34 x 3.96" (553 x 864 x 101 mm)	TS525TU, TS325TU




TA501	Dimensions (HxWxD)	Compatibility
Medium In-Wall Swing Arm Accessory	20 x 30 x 3.96" (508 x 762 x 101 mm)	TS318TU



TA502	Dimensions (HxWxD)	Compatibility
Small In-Wall Swing Arm Accessory	17.2 x 14.25 x 3.96" (437 x 362 x 101 mm)	TS218SU, TS118SU



PAC525FC	Dimensions (HxWxD)	Compatibility
Small Multi-Depth Wall Box	9 x 14.25 x 3.9" (229 x 362 x 99 mm)	All Chief Wall Mounts; Standard & 2.5" (64 mm) depth studs



PAC526FC	Dimensions (HxWxD)	Compatibility
Large Multi-Depth Wall Box	14.25 x 14.25 x 3.9" (362 x 362 x 99 mm)	All Chief Wall Mounts; Standard & 2.5" (64 mm) depth studs



PAC511	Dimensions (HxWxD)	Compatibility
Retrofit Pre-Wire In-Wall Box	18.4 x 16.9 x 3.4" (467 x 419 x 87 mm)	All Chief Wall Mounts



PAC516	Dimensions (HxWxD)	Compatibility
Pre-Wire In-Wall Box	15.5 x 14.5 x 3.5" (394 x 368 x 89 mm)	All Chief Wall Mounts



PAC522	Dimensions (HxWxD)	Compatibility
Pre-Wire In-Wall Box	7.8 x 14.5 x 3.5" (197 x 368 x 89 mm)	All Chief Wall Mounts



PAC521P	Dimensions (HxWxD)	Compatibility
In-Wall Box with Power Outlet Conditioner	11.5 x 7.4 x 3.8" (292 x 188 x 97 mm)	All Chief Wall Mounts