


# ULTIMA®


Tegular  
fine texture



Items 1911, 1912,  
1914, 1915



Ultima Beveled Tegular with Sonata® 9/16" suspension system (Pg. 265)




## KEY SELECTION ATTRIBUTES

- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Scrubbable and water-repellent (items 1936, 1937)
- Excellent sound absorption
- High CAC for excellent sound blocking – items 1951, 1952
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1911HRC, 1912HRC, 1914HRC, 1915HRC. 71% Pre-consumer; 15% Post-consumer
- 88% Biobased content (see page 331)
- Available with AirGuard™ Coating
- Visual coordinates with Optima® for mixed (open/closed plan) applications
- Items 1912 and 1936 available on Create!™ colors and images – see pages 163-165
- Non-directional visual reduces installation time and scrap
- Compatible with the TechZone™ Ceiling Systems
- Meets USDA/FSIS guidelines for use in food processing areas (items 1936 and 1937)
- 30-Year Limited System Warranty against visible sag (excludes items 1905 and 1929), mold/mildew, and bacterial growth

## TYPICAL APPLICATIONS

- Offices
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail
- Areas requiring frequent plenum access
- Areas with indirect lighting systems
- Kitchens, dining rooms, and food preparation areas (items 1936 and 1937)

## DETAIL (Other Suspension Systems compatible. Refer to listing on page 228.)



1. Ultima Beveled Tegular
2. Ultima Health Zone™ Beveled Tegular
3. Ultima with Suprafine® 9/16" suspension system
4. Ultima with Silhouette® XL® 9/16" suspension system with 1/4" reveal

## COLOR



Create! colors available on items 1912, 1936. See pages 165-167.

**ULTIMA®**

**Tegular**  
fine texture

HRC items contain 15% or greater post-consumer recycled ceilings



UP TO **86%** RECYCLED CONTENT

**EPD**  
AVAILABLE

**LEED®**



Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie)

\*LOCATION DEPENDENT



**VISUAL SELECTION**

**PERFORMANCE** Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability						Recycled Content*	Recycle Program	Warranty**
				NRG	CAC						Water Repel	Wash	Scrub	Impact	Scratch	Soil			
<b>ULTIMA Tegular</b>				UL Classified															
15/16" Beveled Tegular	15	<b>1422</b>	6 x 48 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
		<b>1917</b>	12 x 24 x 3/4"	N/A	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>NEW 1993</b>	12 x 48 x 3/4"	0.65	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>NEW 1994</b>	12 x 60 x 3/4"	0.65	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>NEW 1995</b>	12 x 72 x 3/4"	0.65	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>1911</b> <b>1911HRC**</b>	24 x 24 x 3/4" 24 x 24 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High High	•	30
	15	<b>1951</b>	24 x 24 x 3/4"	0.60	40	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>NEW 1894</b>	24 x 24 x 3/4"	0.60	40	Fire Guard	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>1914</b> <b>1914HRC**</b>	24 x 48 x 3/4" 24 x 48 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High High	•	30
	15	<b>1985</b>	24 x 60 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>1981</b>	24 x 72 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
	15	<b>NEW FastSize™</b>	W: 4" - 24" / L: 4" - 72" 3/4" thick	0.60	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
<b>ULTIMA Tegular with AirGuard™ Coating</b>																			
15/16" Beveled Tegular	15	<b>1901</b>	24 x 24 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30
		<b>1904</b>	24 x 48 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	-	•	•	•	High	•	30

\*\* Other sizes are not available for HRC items



MINERAL FIBER



# ULTIMA®

**Tegular**  
fine texture

HRC items contain 15%  
or greater post-consumer  
recycled ceilings



UP TO **86%** RECYCLED  
CONTENT

**EPD**  
AVAILABLE

**LEED®**



Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie)

\*LOCATION DEPENDENT

## VISUAL SELECTION

## PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability					Primary (Embodied) Energy	Recycled Content*	Recycle Program	Warranty†	
				NRC	CAC						Water Repel	Wash	Scrub	Impact	Scratch					Soil
<b>ULTIMA Tegular</b>																				
9/16" Beveled Tegular	29, 44, 48, 52, 56, 60	<b>1423</b>	6 x 48 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>1427</b>	6 x 60 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>1916</b>	12 x 24 x 3/4"	N/A	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>NEW 1996</b>	12 x 48 x 3/4"	0.65	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>NEW 1997</b>	12 x 60 x 3/4"	0.65	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>NEW 1998</b>	12 x 72 x 3/4"	0.65	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>1912</b> <b>1912HRC**</b>	24 x 24 x 3/4" 24 x 24 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High High	•	30
	29, 44, 48, 52, 56, 60	<b>1952</b>	24 x 24 x 3/4"	0.60	40	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>NEW 1895</b>	24 x 24 x 3/4"	0.60	40	Fire Guard	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>1915</b> <b>1915HRC**</b>	24 x 48 x 3/4" 24 x 48 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High High	•	30
	29, 44, 48, 52, 56, 60	<b>1986</b>	24 x 60 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>1982</b>	24 x 72 x 3/4"	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30
	29, 44, 48, 52, 56, 60	<b>1905</b>	30 x 30 x 3/4"	0.70	35	Class A	0.90	•	Std	•	-	•	•	•	•	•	•	High	•	1
	29, 44, 48, 52, 56, 60	<b>1929</b>	30 x 54 x 3/4"	0.70	35	Class A	0.90	•	Std	•	-	•	•	•	•	•	•	High	•	1
	29, 44, 48, 52, 56, 60	<b>NEW FastSize™</b>	W: 4" - 24" / L: 4" - 72" 3/4" Thick	0.70	35	Class A	0.90	•	•	•	-	•	•	•	•	•	•	High	•	30

\*\* Other sizes not available for HRC items.

MINERAL FIBER

# ULTIMA®

**Tegular**  
fine texture

UP TO **77%** RECYCLED CONTENT

**LEED®**

acoustics energy daylight & views indoor air quality renewable materials recycled content waste mgmt local\* materials

EPD AVAILABLE

Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie) \*LOCATION DEPENDENT




## VISUAL SELECTION

## PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability						Primary (Embodied) Energy	Recycled Content*	Recycle Program	Warranty*	
				NRC	CAC						Water Repel	Wash	Scrub	Impact	Scratch	Soil					Below 11MJ/SF
<b>ULTIMA Tegular with AirGuard™ Coating</b>				UL Classified																	
9/16" Beveled Tegular	29, 44, 48, 52, 56, 60	<b>1902</b>	24 x 24 x 3/4"	0.70	35	Class A	0.90	•	•	•	•	•	•	•	•	•	•	•	•	•	30
29, 44, 48, 52, 56, 60		<b>1906</b>	24 x 48 x 3/4"	0.70	35	Class A	0.90	•	•	•	•	•	•	•	•	•	•	•	•	•	30
<b>ULTIMA Health Zone™</b>																					
15/16" Beveled Tegular	15, 16	<b>1937</b>	24 x 24 x 3/4"	0.70	35	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•	30
9/16" Beveled Tegular	29, 44, 48, 52, 56, 60	<b>1936</b>	24 x 24 x 3/4"	0.70	35	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•	30

## SUSPENSION SYSTEMS



Item 1912-CAC 33 on Interlude, Sonata, Suprafine

### NEW Blizzard White – Suspension System Finish

A color and texture coordinated suspension system to complement Ultima ceiling panels for a monolithic look and feel. Available for:

1. Prelude XL and XL HRC
2. Suprafine ML, XL, and XL HRC
3. Silhouette XL 1/4" and 1/8" Reveal
4. Interlude XL HRC



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane. 1936, 1937 – Wet-formed mineral fiber with DuraBrite acoustically transparent water-repellent membrane.

**Surface Finish**  
DuraBrite with factory-applied latex paint

**Fire Performance**  
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

**ASTM E1264 Classification**  
Type IV, Form 2, Pattern E  
Fire Class A

**Sag Resistance**  
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications. (Excludes items 1905 and 1929).

**Anti-Mold/Mildew & Bacteria**  
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

**VOC Emissions**  
Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Primary (Embodied) Energy**  
See all LCA information on our EPD's.

**High Recycled Content\***  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor – 2.2 (BTU units)  
R Factor – 0.39 (Watts units)

**30-Year Performance Guarantee & Warranty\***  
When installed with Armstrong Suspension System. Details at [armstrong.com/warranty](http://armstrong.com/warranty)

**Cleaning Recommendations (Items 1936, 1937 only)**  
To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth. Acceptable colorless disinfectants include:

- Sodium hypochlorite
- Hydrogen peroxide
- Quaternary ammonium

**Weight: Square Feet/Carton**  
1905 – 1.05 lbs/SF; 62.5 SF/ctn  
1911, 1912, 1914, 1915 – 1.05 lbs/SF; 48 SF/ctn  
1916, 1917, 1993, 1996 – 1.05 lbs/SF; 24 SF/ctn  
1936, 1937 – 1.08 lbs/SF; 48 SF/ctn  
1422, 1423 – 1.08 lbs/SF; 24 SF/ctn  
1427 – 1.07 lbs/SF; 24 SF/ctn  
1929 – 1.02 lbs/SF; 68 SF/ctn  
1951, 1952 – 1.31 lbs/SF; 48 SF/ctn  
1901, 1902, 1904, 1906 – 1.08 lbs/SF; 48 SF/ctn  
1994, 1997 – 1.05 lbs/SF; 30 SF/ctn  
1995, 1998 – 1.05 lbs/SF; 36 SF/ctn

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
1905M, 1912M, 1912MHRC, 1914M, 1915M, 1916M, 1917M, 1951M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

**TechLine™ / 1 877 ARMSTRONG**  
[armstrong.com/commceilings](http://armstrong.com/commceilings)  
(search: ultima)  
BPCS-3039-814

LEED® is a registered trademark of the U.S. Green Building Council  
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2014 AWI Licensing Company  
Printed in the United States of America

