

UNIVERSAL STYLE STEAM TRAPS

WSIB450

Watson McDaniel reserves the right to change the designs and/or materials of its products without notice.
©2010 Watson McDaniel Company

Inverted Bucket **Steam Trap Module** (mounts to Universal Connectors)

Model	WSIB450, WSIB450H
Connections	Fits WU450 Series universal connectors
Body Material	Stainless Steel
PMO Max. Operating Pressure	450 PSIG*
TMO Max. Operating Temperature	800°F
PMA Max. Allowable Pressure	720 PSIG @ 100°F
TMA Max. Allowable Temperature	800°F @ 400 PSIG

*750°F @ operating pressures below 400 PSIG. See installation note regarding using trap in superheated applications.

Steam trap modules can be used with other manufacturers' Universal Connectors.

TYPICAL APPLICATIONS

DRIP, TRACER: The **WSIB450** inverted bucket steam trap module, mounted to a universal connector, is typically used for drip and tracing applications. Also used on process equipment with light loads and where air removal is not critical. The WSIB450 trap module mounts to any universal connector.

HOW IT WORKS

The universal connector is permanently installed into the pipeline where the steam trap would normally be placed. The trap module is bolted to the universal connector with two bolts and sealed with a gasket. When a new trap module is needed, it can be easily removed and replaced with a standard open-end or socket wrench without disturbing the existing piping.

SAMPLE SPECIFICATION

The steam trap shall be an all stainless steel modular design, inverted bucket type with a frictionless valve lever assembly. The trap shall have a 360 degree swivel mount on a stainless steel Universal Connector that is available with integral strainer and blowdown valve options.

INSTALLATION & MAINTENANCE

Trap module must be installed in orientation shown. Installation should include isolation valves. With superheated steam, a check valve must be installed at inlet of trap. For full maintenance details, see Installation and Maintenance Manual.



**WSIB450
Inverted Bucket
Steam Trap
Module**

OPTIONS

Universal Connectors are available with an integral strainer and blowdown valve. Connector is purchased separately. See the WU450 Universal Connectors section for more information.

FEATURES

- Trap module can be easily removed and replaced in minutes without having to disconnect any piping
- Hardened stainless steel valves and seat
- Freeze resistant
- Connectors available with integral strainers and blowdown valves
- 360° swivel design for convenient installation

MATERIALS

Body	Stainless Steel GR CF3
Cover	304L Stainless Steel
Internals	300 Series Stainless Steel
Valve Plug & Seat	420F Stainless Steel
Bolts	ASTM A193 GR B7
Gasket	Spiral-Wound 304 Stainless Steel with Grafoil Filler
Swivel Flange	303 Stainless Steel

CAPACITIES – Condensate (lbs/hr)

Model	Orifice Size	PMO (PSIG)	Differential Pressure (PSI)																																									
			5	10	15	20	25	30	40	50	60	70	80	100	125	150	180	200	250	350	450																							
WSIB450-20	3/16"	20	450	560	640	690																																						
WSIB450-80	1/8"	80	300	350	400	440	460	500	550	580	635	660	690																															
WSIB450-150	#38	150	210	250	280	300	320	350	380	400	420	450	470	500	550	570																												
WSIB450-450	.057	450	31	50	70	84	95	105	120	133	145	152	160	174	187	198	208	215	228	248	263																							
WSIB450H-15	1/4"	15	830	950	1060																																							
WSIB450H-30	3/16"	30	530	700	820	880	950	1000																																				
WSIB450H-70	5/32"	70	380	500	560	620	680	710	770	840	900	950																																
WSIB450H-125	1/8"	125	285	375	440	485	530	560	620	670	720	780	800	860	950																													
WSIB450H-200	7/64"	200	205	265	315	350	385	410	465	500	580	590	620	650	700	810	840	860																										
WSIB450H-250	#38	250	155	205	240	270	295	320	360	400	500	530	550	580	630	660	690	710	760																									
WSIB450H-450	.057	450	31	50	70	84	95	105	120	133	145	152	160	174	187	198	208	215	228	248	263																							