

BACKFLOW PREVENTION CATALOG

Double Check Valve Backflow Preventers

DCLF 4An SERIES



n Flow



Sizes 2-1/2" - 12"



TriForce™ Check



Optional Valve Setter (see pg 50)

n STYLE DOUBLE CHECK VALVE ASSEMBLY

The Apollo® MODEL DCLF 4An Double Check Valves are designed to prevent contamination of the potable water supply due to back-siphonage or backpressure from substances that are objectionable, but non-health hazards. The TriForce™ center stem guided check valves feature replaceable and reversible silicone seat discs. The normally vertical up/vertical down oriented body incorporates an internal swivel connection providing the ability to pivot the second check. The n style flow body is domestic stainless steel from 2-1/2"-8" and FDA epoxy coated ductile iron in the 10" and 12". Available in a wide variety of shut-off valves.

OPERATION

During normal flow conditions, the two check valves are held off their seats, supplying water downstream. Each check valve is designed to maintain a minimum of 1 psi across the valve during normal operation. Should the downstream pressure increase to within 1 psi of supply pressure, both check valves will close to prevent a backflow condition.

FEATURES

- Domestic Stainless steel body: 2-1/2"-8"
- FDA epoxy coated ductile iron body: 10" & 12"
- Easy maintenance - no special tools required
- Drop-in check retainers: 2-1/2"-6"
- Bolted-in checks: 8"-12"
- Low pressure loss as documented by an independent laboratory
- Center stem guided TriForce™ check valves
- 5 year, domestic warranty
- **Lead-Free** standard
- Small installation space required - small footprint
- Chloramine-resistant elastomers
- Approved by the Foundation for Cross-Connection Control and Hydraulic Research at the University of Southern California (2-1/2" - 8")
- ASSE 1015
- UL, ULC Classified
- FM approved
- Maximum working pressure 175 psi
- Temperature range 33°F - 140°F, 180°F intermittent
- Optional valve setters eliminate need for thrust blocks
- US Patent Nos. 6,443,184; 7,025,085; 7,533,699
- Made in the USA

MATERIALS

Part	Material
Body (2-1/2"-8")	304 Stainless Steel
Body (10 & 12")	FDA Epoxy Coated Ductile Iron
Covers (2-1/2"-6")	Glass Filled PPO/SS
Covers (8")	304 Stainless Steel
Covers(10 & 12")	FDA Epoxy Coated Ductile Iron
Check Valves	Bronze/Glass-filled PPO/SS
Springs	Stainless Steel
Seat Discs	Chloramine-resistant Silicone

FACTORY CODE

4AnLF	1 X	X	OX
	Y-STRAINER	SIZE	SHUT-OFF VALVES
4AnLF = Lead Free Standard	0 = Standard 1 = w/Y-strainer (shipped loose)	9 = 2-1/2" 0 = 3" A = 4" C = 6" E = 8" G = 10" H = 12"	1 = Less Shut-off Valves 2 = NRS Flg x NRS Flg 3 = OS&Y Flg x OS&Y Flg 4 = OS&Y Flg x Monitored (Mon.) Butterfly Vlv Grv [†] 6 = OS&Y Flg x Post indicator Flg** 7 = OS&Y Flg x OS&Y Grv 8 = OS&Y Grv x OS&Y Grv 9 = Mon. Butterfly Vlv Grv x Mon. Butterfly Vlv Grv [†] 10 = OS&Y Flg x Post Indicator Grv** 11 = NRS Grv x NRS Grv 12 = NRS Flg x NRS Grv 13 = Post Indicator Flg x Mon. Butterfly Vlv Grv [†] 14 = Post Indicator Flg x Post Indicator Flg 16 = Mon Butterfly Vlv Grv x Post Indicator Flg [†] 17 = Post Indicator Flg x OS&Y Grv 18 = OS&Y Grv x Post Indicator Grv 19 = Mon. Butterfly Vlv Grv x Post Indicator Grv 20 = Post Indicator Flg x OS&Y Flg ** Post indicator with plate & nut option not available in 2-1/2" size. [†] Butterfly valves not available in 12" size.

Example:
4AnLF 10A 03 = 4" size Lead Free Double Check Valve Assembly with OS&Y flanged inlet x OS&Y flanged outlet shut-off valves (shown above)

www.apollovalves.com

Customer Service (704) 841-6000

