DIAGNOSTICS, INSPECTION & LOCATING

Reels & Cameras





Accessories

Catalog No.	Description
35338	45 mm Pipe Guide, Fits 25 mm Camera (pkg. of 2)
40598	60 mm Pipe Guide, Fits 25 mm Camera (pkg. of 2)
46708	85 mm Pipe Guide, Fits 25 mm Camera (pkg. of 2)
46713	125 mm Pipe Guide, Fits 25 mm Camera (pkg. of 2)
47793	36 mm Pipe Guide, Fits 25 mm Camera (pkg. of 1)

Replacement Parts

Catalog No.	Description	
43138	RM200 Camera Head NTSC	

SeeSnake® MAX rM200 Series

The rM200 Camera System combines portability with the versatility of the D2 drum series, offering different combinations of push cable stiffness and spring flexibility to tackle any inspection job.

Interchangeability

- The D2 drum series currently consists of the D2A and D2B drums.
- The rM200 comes with your choice of drum.
- Either drum can be purchased separately.
- Own them both; quickly and easily interchanged giving you on-the-job flexibility.

Pushability

- Drums feature different push cable lengths, diameters, stiffness and springs.
- Chose the drum that enables you to easily negotiate turns and tees there's a drum that's right for you!

Portability

- Easy to transport; via its wheels or carry handle.
- Dock the CS6 or CS65 digital monitor for convenient transport, operation and storage.

-M7200A

- System Weight 36.3 lb (16.5 kg).
- Drum Weight 16.4 lb (7.4kg).
- Drum Diameter 17" (43.2 cm).
- Camera View Self-leveling.
- Length 1" (2.6 cm).
- Diameter 1" (2.5 cm).
- Light 6 LEDs.
- Sonde Frequency 512 Hz.
- Resolution NTSC 656 x 492 Pixels; PAL 768 x 576 Pixels.
- Spring Assembly Type Single.
- Length 12" (30.8 cm).
- Push Cable Length 200' (61 m).
- Diameter 0.3" (0.76 cm).
- Fiberglass Core Diameter 0.14" (0.36 cm).
- Minimum Bend Radius 2.8" (7.1 cm).
- Pipe Capacity when used with a 5" (12.5 cm) pipe guide. 1.5" to 8" (3.8 cm to 20.3 cm).

rM200B

- System Weight 39.2 lb (17.8 kg).
- Drum Weight 19.2 lb (8.7kg).
- Drum Diameter 17" (43.2 cm).
- Camera View Self-leveling.
- Length 1" (2.6 cm).
- Diameter 1" (2.5 cm).
- Light 6 LEDs.
- Sonde Frequency 512 Hz.
- Resolution NTSC 656 x 492 Pixels; PAL 768 x 576 Pixels.
- Spring Assembly Type Dual Nested.
- Length 17" (43.3 cm).
- Push Cable Length 165' (50 m).
- Diameter 0.35" (0.90 cm).
- Fiberglass Core Diameter 0.18" (0.45 cm).
- Minimum Bend Radius 3.5" (8.9 cm).
- Pipe Capacity when used with a 5" (12.5 cm) pipe guide. 2" to 8" (5.1 cm to 20.3 cm).

Catalog	Model No.	Description	Weight	
No.			lb.	kg
42348	rM200A	Reel, SeeSnake MAX rM200A w/D2A Drum	363/10	16.50
47528	rM200B	Reel, SeeSnake MAX rM200B w/D2B Drum	391/5	17.80
47538	rM200	Drum, rM200 D2B	19 ¹ /5	8.70
47548	rM200	Drum, rM200 D2A	16 ² / ₅	7.40

