

2 ■ CUTTING / SAWING / CORE DRILLING / REAMING / GAUGING

HACKSAW FRAME

0490 : Hacksaw frame

For 300 mm blades.

Hacksaw Frame (049000): 4 blade positions.
Supplied with HSS bi-metal blade (12 teeth/cm).

Hacksaw Frame With Finger-Protecting Closed Grip (049050): 3 blade positions.
Spare blade storage in the upper frame.
Supplied with HSS bi-metal blade (12 teeth/cm).

Mini Hacksaw Frame(049070): Special grip for use where standard hacksaw cannot reach.
Supplied without blades.



Description	Size mm	Kg	Ref.
Hacksaw frame	500 x 125	0,590	049000
Hacksaw Frame With Finger-Protecting Closed Grip	425 x 130	0,630	049050
Mini Hacksaw Frame	105 x 80	0,050	049070

SAW BLADE

0430 : HSS Saw Blade

New High speed and precise HSS bi-metal saw blade:

- 18 teeth or 24 teeth per inch : blade perfect for steels, but also aluminium, stainless steel, PCV or wood, high thickness (18 TPI) or medium thickness (24 TPI)
- 32 teeth: blade perfect for copper, but also aluminium and stainless steel, small thickness.

Overheating resistance: high longevity.

Flexible blade to be able to cut in difficult to access locations.



Use	Number of teeth per "	Number of teeth per cm	Recommended thickness mm	L mm	Packaging	Kg	Ref.
Steel	18	8	6-25	300	10	0,174	043003
Steel	18	8	6-25	300	50	0,965	043007
Steel	18	8	6-25	300	100	1,740	043008
Steel	24	10	3-6	300	10	0,174	043004
Steel	24	10	3-6	300	50	0,965	043009
Steel	24	10	3-6	300	100	1,740	043010
Copper	32	12	1-3	300	10	0,174	043006
Copper	32	12	1-3	300	50	0,965	043011
Copper	32	12	1-3	300	100	1,740	043012