

1375 : Phenix III Portable Electric Threader



For effortless threading up to 2" in all situations.
Holding vice with anti-torque bar to steady the machine
during threading operations.
Ideal for working in confined spaces (close to walls, etc.).



4

Bidirectional rotation.

Mechanical reverse control ensuring longer motor life.

Adaptor for octagonal heads 1/8" to 1 1/4" with unique locking system for securely holding the head during difficult operations.

Rotation speed: 26 rpm in both directions.



Description	Voltage V	Power	Kg	Ref.
Phenix III + 4 Right heads BSPT: 1/2" - 3/4" - 1" - 1.1/4"	230	1100W - 50/60 Hz	18,800	137562
Phenix III + 6 Right heads BSPT: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2"	230	1100W - 50/60 Hz	22,800	137563

Capacities

Steel:

Right BSPT Ø 1/8 to 2"

Left BSPT Ø 1/8 to 2"

NPT: Ø 1/8 to 2"

Stainless steel:

Right BSPT : Ø 1/8 to 2".

Delivered with

- 1 holding vice (ref. 137552)

- 1 adaptor for octagonal heads 1/8" to 1 1/4" (ref. 137553).

Tips

Virax cutting oil (ref. 110200) should be used for smooth die operation, ensuring a good cut and a perfect thread.



Virax and the environment

Virax is committed to environmental protection and sustainable development. From product design to delivery, Virax controls its environmental impact.

Compliance with the REACH Directive No.1907/2006.

Reduced energy consumption.

Dematerialisation of documentary flows and control over printing.

Waste reclaiming.

Our packaging materials are recycled through our partnership with Eco Emballage.