

# 3 ■ BENDING

## BENDING PLIERS

### 2511 : Bending Pliers

For hardened and annealed copper pipes: Ø 6 to 18 mm and Ø 1/4" to 5/8" O.D. / wall thickness 1 to 1.2 mm.

Bending radius: 2 to 3.5 D.

**For forming very short radius bends and counter-bends.**

Bending angle: up to 180°.

0 to 180° graduations.

Steel handle and body. Machined groove.



Pipe O.D.	Bending radius mm	Kg	Ref.
6	11	0,310	<b>251106</b>
8	14	0,355	<b>251108</b>
10	23	0,850	<b>251110</b>
12	30	1,000	<b>251112</b>
14	42	2,100	<b>251114</b>
15	42	2,100	<b>251115</b>
16	54	2,740	<b>251116</b>

Pipe O.D.	Bending radius mm	Kg	Ref.
18	55	3,000	<b>251118</b>
1/4	15	0,355	<b>251121</b>
5/16	25	0,500	<b>251122</b>
3/8	35	1,015	<b>251123</b>
1/2	45	2,100	<b>251124</b>
5/8	54	2,700	<b>251125</b>

### 2514 : Bending pliers

For hardened and annealed copper pipes: Ø 8 to 16 mm / wall thickness: 1 to 1.2 mm.

Bending radius: approx. 3.85 D.

**Lightweight alloy body.**

**Rounded shape, can rest on the knee.**

180° bending angle.

Handles designed for clamping in a parallel vice.



Pipe O.D. mm	Bending radius mm	Kg	Ref.
8	35	0,490	<b>251408</b>
10	40	0,925	<b>251410</b>
12	45	0,850	<b>251412</b>
14	50	1,340	<b>251414</b>
15	55	1,385	<b>251415</b>
16	60	1,730	<b>251416</b>



### Much more than just quality, here's the Virax commitment!

Virax commits to total, permanent and durable satisfaction of users and therefore applies a process based on:

- A proactive product plan.
- A constant innovation process.
- A focus on permanent improvement.
- Improved customer services.
- An assurance of optimum availability rate.

**Customer satisfaction, the heart of our commitments.**