

0170 : Adjustable Wrench

Triple coating of nickel and chrome provides high corrosion resistance. Very tough. The moving jaw of 6, 8, 10 and 12" long wrenches do not protrude when open, making them suitable for use in confined spaces.



1

Accross flats A mm	Accross flats A"	E mm	E1 mm	L mm	L "	Kg	Ref.
19	3/4	6	10	150	6	0,120	017006
24	15/16	7	12	200	8	0,230	017008
29	1.1/8	8	14	250	10	0,390	017010
33	1.1/4	11	19	300	12	0,670	017012
45	1.3/4	18	25	380	15	1,230	017015
53	2.1/16	19	28	455	18	2,105	017018

RADIATOR WRENCH

2204 : Radiator Key Wrench With Ratchet

For fitting the captive nuts connecting the regulating valve to the radiator. Short wrench for working on ribbed nuts and internal hexagonal nuts in confined spaces.

Description	Kg	Ref.
Wrench : 3/8" - 1/2" - 3/4" - 1", 1/2" female ratchet	0,545	220425
Wrench : 8 sizes including 3/8" - 1/2" - 3/4" - 1", 1/2" female ratchet	0,560	220435
1/2" female ratchet	0,420	220410
Wrench : Ø 3/8" - 1/2" - 3/4" - 1"	0,130	220420
Wrench : 8 sizes. including 3/8" - 1/2" - 3/4" - 1"	0,140	220430



2204 : Radiator Key Wrench

For fitting the captive nuts connecting the regulating valve to the radiator. 18 mm square drive. Forged steel.

Description	Kg	Ref.
Wrench : Ø 3/8" - 1/2" - 3/4"	0,175	220460
Wrench : Ø 3/8" - 1/2" - 3/4" - 1" - 1.1/4"	0,315	220465



Virax Experts

Would you like technical assistance?

Our team of experts is at your disposal to provide you with tips and recommendations on how to get the most out of your Virax products.

From 8.00 am to 12.15 pm and from 1.45 pm to 5.00 pm, Monday to Friday (4.30 pm): +33 (0) 3.26.59.56.82

Exploded views and manuals: www.virax.com, Documentation section.