

# DUPLEX CONTROL PANELS

Single Phase, 200/230 volt,  
for Sewage, Effluent & Non-Clog  
Pumps w/ Start Components



- Enclosure** Type 4X polycarbon
- Circuit breaker** For pump and control circuit
- Contactor** Definite purpose
- HOA switch** Three position toggle HP rated
- Alarm switch** Three position toggle HP rated
- Run light** Amber neon pilot light
- Start components** Potential relay and capacitors
- Alternating relay** With lead selector switch
- Moisture sensor\*** Seal fail circuit and light
- Temp sensor\*** Heat sensor connections
- Bracket** Bright aluminum
- Fuse** Control and alarm sized at 3 amps
- Terminal strip** Box type lugs sectional
- Wiring** Color coded
- Visible alarm** 360 degree flashing
- Audible alarm** Piezo buzzer with silence switch
- Level control** Requires 4 floats rated at 2 amps
- Certifications** UL 508A

\* Requires sensor to be in pump.

Consult factory for other available options. Some options may require an increase in the enclosure size.

| Volts | Phase | Amps | Part number   |
|-------|-------|------|---------------|
| 200   | 1     | 20   | BP01CD4XNM020 |
| 230   | 1     | 20   | BP21CD4XNM020 |
| 230   | 1     | 40   | BP21CD4XNM040 |

NOTE: Overloads must be located in pump.

