

## PORTABLE ELECTRIC BENDING MACHINE

### 2518 : Portable Battery-Powered Bender Eurostem® II



**For small and medium-sized series in the workshop or on site...**

**Self-contained:** 2 batteries (supplied) provide sufficient power for several hundred bends.

**Accurate** bends ensured by speed-reducer.

**Handy mobile hook** for easy pipe installation and removal.

Bending radius in accordance with European standard EN 1057. Bends up to 180°.

**Motor drive:** - 14.4 V – 2,4 Ah Li-Ion battery. - Bending speed: 0 to 4 rpm.

\* For PEX/AL/PEX pipes



3

| Formers Ø                 | Counter former Ø         | Kg     | Ref.           |
|---------------------------|--------------------------|--------|----------------|
| 12 - 14 - 16 - 18 - 22 mm | 12/15 - 14/16 - 18/22 mm | 16,400 | <b>251800</b>  |
| 12 - 15 - 18 - 22 mm      | 12/15 - 18/22 mm         | 15,000 | <b>251805</b>  |
| 16 - 20 - 26 - 32 mm      | 14/16 - 20 - 26 - 32 mm  | 15,000 | <b>251806*</b> |
| 15 - 22 - 28 mm           | 12/15 - 18/22 - 28 mm    | 15,000 | <b>251845</b>  |
| 15 - 18 - 22 mm           | 12/15 - 18/22 mm         | 14,000 | <b>251846</b>  |
| 14 - 16 - 18 - 22 - 28 mm | 14/16 - 18/22 - 28 mm    | 17,800 | <b>251854</b>  |
| 1/2 - 5/8 - 3/4 - 7/8"    | 1/2 - 5/8 - 3/4 - 7/8"   | 14,000 | <b>251850</b>  |



#### Capacities

##### Maximum capacity:

- Hard copper, locksmith and hydraulic pipes: Ø 10 to 28 mm, wall thickness 1 to 1.5 mm.
- Stainless steel: Ø 10 to 22 mm, wall thickness 1 mm, Ø 28 mm, wall thickness 1.2 mm.
- PEX/Al/PEX: Ø 14 à 32 mm.

#### Delivered with

- 2 Li-Ion batteries 14.4 V - 2.4 Ah.
- 1 fast 45 min. charger.
- in a case.



### Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery?  
From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

#### FRANCE

Phone: 03.26.59.56.78

Fax: 03.26.59.56.20

Email: [client.fr@virax.com](mailto:client.fr@virax.com)

#### EXPORT

Phone: +33 3.26.59.56.97

Fax: +33 3 26.59.56.70

Email: [export@virax.com](mailto:export@virax.com)

**Exploded views and manuals:** [www.virax.com](http://www.virax.com), Documentation section.