

### 3 ■ BENDING

#### 2518 : Portable Power Bender Eurostem® II



**For small and medium-sized series in the workshop or on site...**

**Accurate** bends ensured by speed-reducer.

**Handy mobile hook** for easy pipe installation and removal.



Bending radius in accordance with French standard EN 1057. Bends up to 180°.

**Motor drive:** 230 V - 50/60 Hz - 550 W. - Bending speed: 0 to 3 rpm.

\* For PEX/AL/PEX pipes

Formers Ø	Counter former Ø	Kg	Ref.
12 - 14 - 16 - 18 - 22 mm	12/15 - 14/16 - 18/22 mm	14,170	<b>251802</b>
12 - 15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	<b>251807</b>
16 - 20 - 26 - 32 mm *	14/16 - 20 - 26 - 32 mm *	15,000	<b>251808</b>
15 - 22 - 28 mm	12/15 - 18/22 - 28 mm	15,000	<b>251847</b>
15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	<b>251848</b>
14 - 16 - 18 - 22 - 28 mm	14/16 - 18/22 - 28 mm	16,000	<b>251856</b>
1/2 - 5/8 - 3/4 - 7/8"	1/2 - 5/8 - 3/4 - 7/8"	14,000	<b>251852</b>



#### Capacities

##### Maximum capacity:

- Hard copper, locksmith and hydraulic pipes: Ø 10 to 28 mm, wall thickness 1 to 1.5 mm.
- Stainless steel: Ø 10 to 22 mm, wall thickness 1 mm, Ø 28 mm, wall thickness 1.2 mm.
- PEX/Al/PEX: Ø 14 à 32 mm.

#### Delivered with

- in a case.

#### 2518 : Tripod for Eurostem® II

Kg	Ref.
6,400	<b>251809</b>



#### Safety, one of the top concerns of Virax

##### Safety is a vital concern in the Virax production site:

- Build awareness, communicate and train in risks.
- Develop the risk prevention process.
- Target zero accident.
- Monitor safety equipment.