

HIGH PRESSURE GAUGE GLASS WASHERS (FOR BOILER WATER GAUGES & LIQUID LEVEL GAUGES)

SELF-SEALING MODELIP

EPDM COMPOSITION

For Steam and Water

Made only in the following sizes:



MODEL EFI 66

Washer No.	Dimensions in Inches		
	Inside Diameter	Outside Diameter	Thickness or Height
300	3/8	13/16	1/4
10	1/2	13/16	9/32
210	1/2	7/8	3/8
20	1/2	7/8	1/2
290	1/2	1	5/16
280	1/2	1	3/8
340	1/2	1-7/16	3/8
190	9/16	13/16	9/32
120	9/16	27/32	19/32
180	9/16	1-3/32	1/2
30	5/8	7/8	9/32
520	5/8	7/8	3/8
130	5/8	15/16	9/32
90	5/8	15/16	9/16
40	5/8	1	9/32
250	5/8	1	15/32
50	5/8	1-1/8	3/8
370	5/8	1-1/4	1/2
350	5/8	1-5/16	13/32
500	21/32	1-1/4	1/4
200	11/16	1	9/32
510	11/16	1-1/8	3/8
420	11/16	1-3/16	7/16
440	11/16	1-3/8	3/8
560	11/16	1-7/16	13/32
570	3/4	15/16	3/8
310	3/4	1	3/8
430	3/4	1	3/4
60	3/4	1-1/16	9/32
150	3/4	1-1/16	1/2
470	3/4	1-1/16	3/4
240	3/4	1-3/32	13/32
140	3/4	1-1/8	3/8
390	3/4	1-1/8	7/16
330	3/4	1-1/8	1/2
170	3/4	1-1/8	5/8
540	3/4	1-1/8	7/8
110	3/4	1-3/16	13/32
220	3/4	1-1/4	1/4
70	3/4	1-1/4	13/32
530	3/4	1-1/4	1/2
230	3/4	1-1/4	3/4
80	3/4	1-5/16	13/32
160	3/4	1-5/16	5/8
410	3/4	1-3/8	3/8
320	3/4	1-3/8	1/4
100	3/4	1-7/16	13/32
460	3/4	1-5/8	1/2
450	3/4	1-15/16	3/8
270	7/8	1-3/8	13/32
550	7/8	1-31/64	7/8
400	31/32	1-3/4	3/8
480	31/32	1-3/4	7/16
260	1	1-5/8	1/2
380	1	1-1/2	1
360	1-1/4	1-7/8	1-5/16
490	1-7/8	2-1/4	3/4

MODELAST

NEOPRENE COMPOSITION

For Steam, Water Service and other applications



MODEL EFI 88


Dimensions in Inches			
Glass Outside Diameter	A Inside Diameter	B Outside Diameter	C Thickness or Height
1/2	7/16	3/4	1/4 OR 3/8
1/2	1/2	1-1/8	1/4 OR 3/8
1/2	7/16	1-3/8	1/4 OR 3/8
5/8	9/16	3/4	1/4, 3/8, 1/2 OR 1
5/8	9/16	13/16	1/4, 5/16, 3/8, 1/2 OR 1
5/8	9/16	7/8	1/4, 3/8, 1/2 OR 1
5/8	9/16	15/16	1/4 OR 3/8
5/8	9/16	1	1/4, 3/8, 1/2 OR 1
5/8	9/16	1-1/8	1/4, 3/8, 1/2 OR 3/4
5/8	9/16	1-5/32	1/4, 3/8, 1/2 OR 5/8
5/8	9/16	1-1/4	1/4, 3/8 OR 1/2
5/8	9/16	1-3/16	1/4, 3/8, 1/2 OR 1
3/4	11/16	29/32	1/4 OR 3/8
3/4	11/16	1	1/4, 3/8, OR 1/2
3/4	11/16	1-1/16	1/4 OR 3/8
3/4	11/16	1-1/8	1/4 OR 3/8
3/4	11/16	1-5/32	1/4, 3/8, 1/2 OR 5/8
3/4	11/16	1-15/32	1/4, 3/8, 1/2 OR 3/4
3/4	23/32	7/8	1/4, 3/8, 1/2 OR 1
3/4	23/32	15/16	1/4, 3/8 OR 1/2
3/4	23/32	1-1/16	1/4 OR 3/8
3/4	23/32	1-1/8	1/4, 3/8 OR 1/2
3/4	23/32	1-3/16	1/4, 3/8, 1/2 OR 1
3/4	23/32	1-1/4	1/4, 3/8, 1/2, 5/8 OR 1
3/4	23/32	1-9/32	1/4, 3/8, 1/2, 3/4, 1, OR 1-1/8
3/4	23/32	1-5/16	1/4, 3/8, 1/2 OR 1
3/4	23/32	1-3/8	1/4 OR 3/8
3/4	3/4	15/16	1/4, 3/8 OR 1/2

Other sizes available, contact Ernst Flow Industries.

Any size can be furnished to fit all type Packing Nuts and Glass on Boiler Water Gauges and Liquid Level Gauges.

Gasket Material	Temperature Ratings
NEOPRENE (EFI 88)	-45°F TO 250°F
EPDM (EFI 66 and EFI 33CS)	-65°F TO 300°F
GRAPHITE (EFI 99)	550°F
PURE PTFE (EFI 101)	450°F
PTFE composition (soft)	500°F
BUNA-N	-45°F TO 250°F
FKM	-20°F TO 400°F
PTFE ENVELOPE w/ neo. filler	250°F
PTFE ENVELOPE w/ non-asbestos filler	450°F
NON-ASBESTOS	700°F
GRAPHITE	800°F

SPECIFY:
A. Inside Diameter
B. Outside Diameter
C. Thickness or Height



Note: For Washer compatibility regarding specific requirements and applications...consult with Ernst Flow Industries.


FLAT MICA GASKETS

Helps prevent rubber washer from sticking to Stuffing Boxes, Packing Nuts and Gauge Glass Glands

For use with any tubular glass with No. 66 or 88 washers

- Thickness: .005"

Order 2 Mica Gaskets for each Rubber Washer



MODEL EFI 5