

Capacity: 210g-310g Readability: 0.001 g

Standard Features

- Pill-counting feature also complies with Handbook 44 requirements
- Fast, Super Hybrid Sensor (SHS) gives you the ultimate in response speed; just one second
- Nine weighing modes
- GLP/GMP/ISO compliance
- WinCT® communication tools software included
- Tough die-cast aluminum housing
- Removable stainless steel pan 5 in x 5 in (127 mm x 127 mm)
- NTEP Certified and Pharmacopoeia approved
- IP54 splash proof operator keyboard protects against dust and spills, stainless steel weigh pan
- Data memory function
- Vacuum Fluorescent Display (VFD)
- RS-232



APPROVALS



Specifications

		GF-200P [^]	GF-300P [^]
NTEP	Part#	97799	97800
	List Price	\$1,385.00	\$1,650.00
Capacity		210g	310g
Resolution		0.001 g	0.001 g
Operating Modes		Weigh, Count and Percent	
Decimal Ounce		7.40755 x 0.00005 oz	10.93493 x 0.00005 oz
Repeatability		0.001 g	
Linearity		±0.002 g	
Stabilization Time		Approx 1 second (typical in FAST mode)	
Operating Temperature		41°F to 104°F (5°C to 40°C)	
Weighing Chamber		3.6 in H (91.4 mm)	
Pan Size		5 x 5 in (127 mm)	
Dimensions		8.27 x 12.48 x 3.39 in (210 x 317 x 86 mm)	
Weight (Approx.)		2.15 lb (4.6 kg)	
Est. Ship Weight		11 lb (5.2 kg)	
Power		110/220V VAC adapter	
Approvals		NTEP CC 04-077 e=0.01g	
Warranty		Five-year Limited Warranty	
Return Policy		A&D Weighing Standard Policy - restock fee may apply	

[^] Weighing Chamber

Part Number/ Price

Part #	Model #	Description (Capacity x Resolution)	Price
97799	GF-200P	210g x 0.001 g	\$1,385.00
97800	GF-300P	310g x 0.001 g	\$1,650.00

Options/Accessories

Part #	A&D Model #	Description	Price
102891	GX-02	USB option	\$155.00
97697	GX-10	Glass breeze break for GF-200 and 300	\$282.00
97703	AX:073003691-S	Protective in-use cover for GF-200/300 (each)	\$22.00
97649	TB:648	AC adapter (120V/220V) standard with unit	\$43.00

1280 Kiosk

Automated Truck Scale System



Optional Features

- Additional A/D cards
- RFID reader
- Credit card reader (U.S. only)
- Currency acceptor (U.S. currency only)
- Internal heater
- Gate control
- Loop detector input

Standard Features

- 12-inch 1280 color touchscreen
- Stainless steel enclosure
- 1,500 NIT display
- Two serial ports RS-232 or RS-485
- Operator prompting
- Formattable tickets
- Transmits weight to remote display
- 120 or 220 VAC
- 460 MB onboard database
- Ethernet TCP/IP
- Web server
- Direct thermal printer

Part Numbers/Price

Part#	Description	Price
Consult	1280 Kiosk, Touchscreen, Direct Thermal Printer	Consult