

evoQ₄ Electromagnetic Meter Elster Protocol Encoder Module



Specification

Protocol	Elster K frame
Encoded digits	6 most significant
Encoder ID	10 digit fixed
Power source	Lithium battery (10 yr)
Environmental rating (with appropriate splice kit)	NEMA 6P / IP68
Cable lengths (bare wire)	30 feet, 90 feet
Optional connectors (25')	Itron In Line Connector™ Nicor Connector™
Compatibility	MegaNet™ Enc MTU Itron™ 60W, 60W-R, 200W, 100W Datamatic™ Firefly, MOSAIC Others, contact AMI provider tech support
Materials module	ABS Resin 3 conductor AWG 22 cable

Six digit resolution

- 1000 US gallons
- 100 Cubic feet
- 1 Cubic Meter


Operation

The evoQ₄ electronic water meter offers users flexibility in output choices. The modular design of the output interface allows utilities to easily retrofit meters to upgrade from direct reading or switch among different output modules. The Elster protocol encoder module is appropriate for interface where Elster mechanical water meters using Invision™ Encoder register connected the meter to the utility Automatic Meter Reading system or Automated Metering Infrastructure. Touch reading via inductive pads is supported as well. Upgrading from Touch reading to AMR does not require a module change.

The module operates via optical interface with the evoQ₄ register output. The meter register and the potted encoder module remain fully protected from water ingress, retaining the outstanding reliability inherent to the evoQ₄ product line. The electronic register information is decoded by the encoder and translated to the ASCII standard frame message. Endpoints and interrogation devices obtain the reading through normal transmission processes.

Optional connection variants include bare wire with field splice kits for indoor or submerged locations, Nicor Connector, or Itron In-Line Connector™.







1. Lift the lid, using a small screwdriver blade, carefully remove the pulser clip.




2. Remove the blank cover by lifting up...



3. ...and then slide out.




4. Fit the Encoder unit in the opposite manner to the cover removal.



5. Replace the securing clip (lugs uppermost).

WARNING: Take care not to dislodge the rubber gasket on the underside of the unit when fitting / removing.



Generic Wire Diagram:

Red: Data
White: V+ (power)
Black: V0 (ground)



United States
Elster AMCO Water, LLC
10 SW 49th Avenue, Building 100
Ocala, FL 34474
T +1 800 874 0890
F +1 352 368 1950
watermeters@us.elster.com

Canada
Elster Canadian Meter Company Inc.
1100 Walker's Line, Suite 101
Burlington, Ontario L7N 2G3
T +1 866 703 7581
F +1 905 634 6705
watermeters@ca.elster.com

Caribbean
Elster AMCO Water, Inc.
P.O. Box 225, Carretera 112 KM 2.3
Isabella, PR 00662
T +1 787 872 2006
F +1 787 872 5427
prwatermeters@pr.elster.com

© 2013 by Elster. All rights reserved.

The company's policy is one of continuous product improvement and the right is reserved to modify the specifications contained herein without notice. These products have been manufactured with current technology and in accordance with applicable AWWA Standards.