

Capacity: 610g-2,610g    Readability: 0.1 g

## Standard Features

- Notched and tiered beams for easy reading
- Positive poise positioning for repeatability
- Magnetically damped
- Zero adjust compensator
- Choice of five weighing platforms: stainless steel pan, polypropylene scoop, stainless steel scoop, aluminum animal box, stainless steel plate
- Optional tare beam vernier dial



## Specifications

	710-00	710-T0	720-00	750-S0	760-00	720-S0
Part#	33350	33351	33352	33355	33357	33353
List Price	\$249.00	\$305.00	\$294.00	\$138.00	\$258.00	\$341.00
Capacity	610 g	610 g	610 g	610 g	610 g	610 g
Resolution	0.1 g	0.1 g	0.1 g	0.1 g	0.1 g	0.1 g
Tare Range	-	225 g	-	-	225 g	-
Pan Design	Stainless steel pan	Stainless steel pan with tare	Polypropylene scoop	Stainless steel plate	Stainless steel plate with tare	Stainless steel scoop
Pan Size	Ø 6 in (152.4 mm)		-	Ø 6 in (152.4 mm)		-
Dimensions	(W x D x H) 18 x 12 x 9 in (457.2 x 304.8 x 228.6 mm)					
Weight (Approx.)	8 lb					
Calibration	Front beam 10 x 0.1 g, Middle beam 500 x 100 g, Rear beam 100 x 10 g					
Warranty	Five-year Limited Warranty					
Return Policy	OHAUS Standard Policy - restock fee may apply					

## Specifications

	730-00	1650-00*	1650-W0*	1610-00*	TP2611
Part#	33354	33361	33362	33360	103109
List Price	\$368.00	\$323.00	\$373.00	\$373.00	\$198.00
Capacity	610 g	610 g	2,610 g	610 g	2,610 g
Resolution	0.1 g	0.1 g	0.1 g	0.1 g	0.1 g
Tare Range	-	225 g	225 g	225 g	-
Pan Design	Aluminum weight boat	Stainless steel plate with tare			Stainless steel pan with rod and clamp
Pan Size	-	6 in (152.4 mm)			5.8 x 5.8 in (147.3 x 147.3 mm)
Dimensions	(W x D x H) 18 x 12 x 9 in (457.2 x 304.8 x 228.6 mm)				
Weight (Approx.)	8 lb (3.6 kg)				
Calibration	Front beam 10 g x 0.1 g, Middle beam 500 g x 100 g, Rear beam 100 g x 10 g				
Warranty	Five-year Limited Warranty				
Return Policy	OHAUS Standard Policy - restock fee may apply				

\*Dial-O-Gram models



**Standard Features**

APPROVALS



- Touchless sensors
- Backlit dual LCD display
- Illuminated up-front level indicator
- Internal rechargeable battery
- ABS plastic housing
- Skid-resistant leveling feet
- Menu lock switch
- Multiple application modes
- RS-232 standard
- Fast stabilizing time

**Specifications**

	V71P1502T	V71P3T	V71P6T	V71P15T	V71P30T
Part#	157316	157317	157318	157319	157320
List Price	\$593.00	\$593.00	\$593.00	\$593.00	\$593.00
Capacity	1.5kg	3kg	6kg	15kg	30kg
Resolution	0.00005 kg	0.0001 kg	0.0002 kg	0.0005 kg	0.001 kg
Weighing Modes	Weighing, Percent, Checkweighing, Accumulation				
Units of Measures	Pound, Ounce, Kilogram, Gram				
Pounds	3 lb x 0.0001 lb	6 lb x 0.0002 lb	15 lb x 0.0005 lb	30 lb x 0.001 lb	60 lb x 0.002 lb
Grams	1,500 g x 0.05 g	3,000 g x 0.1 g	6,000 g x 0.2 g	15,000 g x 0.5 g	30,000 g x 1 g
Ounces	48 oz x 0.002 oz	96 oz x 0.005 oz	240 oz x 0.01 oz	480 oz x 0.02 oz	960 oz x 0.05 oz
NTEP Resolution	3 lb x 0.001 lb	6 lb x 0.002 lb	15 lb x 0.005 lb	30 lb x 0.01 lb	60 lb x 0.02 lb
Operating Temperature	14° F to 104° F/-10° C to 40° C				
Pan Size	11.8 x 8.9 in (300 x 225 mm)				
Dimensions	(W x D x H) 12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)				
Weight (Approx.)	9.2lb. (4.2 kg)				
Power	100-240V, internal rechargeable battery 210-hr operation with 12-hr full charge				
Approvals	NTEP CC 13-022				
Warranty	One-year Limited Warranty				
Return Policy	OHAUS Standard Policy - restock fee may apply				

**Part Number/Price**

Part #	Model #	Description	Price
157316	V71P15025	1.5 kg x 0.00005 kg	\$593.00
157317	V71P3T	3 kg x 0.0001 kg	\$593.00
157318	V71P6T	6 kg X 0.0002 kg	\$593.00
157319	V71P15T	15 kg X 0.0005 kg	\$593.00
157320	V71P30T	30 kg X 0.001 kg	\$593.00

**Options/Accessories**

Part #	Model #	Description	Price
154638	30037447	Ethernet kit	\$122.00