Load Ranger Wireless Wheel Pad Scale



Standard Features

- Up to six individual pads (three sets) per system, completely wireless
- 14 individual pads (seven sets) per system maximum, joined via cable, wireless communication to indicator
- Equipped with industrial Bluetooth® radio module for ability to communicate with indicator
- · Integrated wheels for easy transport and positioning
- Internal rechargeable battery with 40 hours of battery life
- Non-slip rubber on the underside of the platform for good grip on all types of surfaces
- · Built-in indicator on each scale with 1in character display
- IP68 rating
- · Cover plate protects built-in indicator

Remote indicator with integrated printer in carrying case

- Carrying case: 1 ft x 1 ft 6 in x 7 in (325 mm x 460 mm x 170 mm)
- · Backlit graphic display with touch screen technology
- Internal rechargeable battery with 10 hours of battery life
- · Real time clock
- · Permanent data storage
- Slot for built-in micro SD
- 24-bit A/D converter, up to 2,300 conversions per second
- One DB9 RS232 serial port
- Thermal printer
- · ABS transport case

Wheel weighing software

- . Multi-scale functioning mode with ability to weigh up to 14 individual pads (seven sets)
- Static axle weighing function, up to two channels
- · Calculation of the x and y coordinates of the center of gravity
- · Semi-automatic tare
- · Preset tare
- Selection of displayed data on the LCD touchscreen
- · Completely customizable keyboard
- 15 customizable and printable text IDs
- 1,000 field database
- · Programmable printout from keyboard
- Print and display list of last 3,500 vehicle

Options/Accessories

- · Leveling modules
- Pit frames for semi-permanent floor installations
- Aluminum ramps

Specifications

Construction:

Aluminum alloy

Display:

1 in character display on each scale

Platform Dimensions (I x w x h):

Load Ranger RF-MD: 1ft 10 in x 1 ft 8 in x 2.28 in (564 mm x 511 mm x 58 mm)
Load Ranger RF-WD: 2ft 6 in x 1 ft 10 in x 2.28 in (750 mm x 561 mm x 58 mm)
Load Ranger RF-XWD: 3ft 1 in x 2 ft x 2.28 in (950 mm x 611 mm x 59 mm)

Loading Surface (I x w):

Load Ranger RF-MD: 1ft 10 in x 1ft 4 in (564 mm x 400 mm)
Load Ranger RF-WD: 2ft 6 in x 1ft 6 in (750 mm x 450 mm)
Load Ranger RF-XWD: 3ft 1 in x 1ft 8 in (950 mm x 500 mm)

System Accuracy:

0.05% of rated capacity

Power Supply:

Rechargeable battery Approximately 40 hours of battery life Includes uL approved AC wall adaptor

Operating Temperature:

14°F to 104°F (-10°C to 40°C)

Storage Temperature:

-4°F to 140°F (-20°C to 60°C)

Warranty:

2 year limited warranty



Part Number/Price

Part #	Description		Price
182099	Remote indicator with integrated printer in carrying of	case	\$1,595.00
Part #	Size	Graduation	Price
Load Ranger RF-	MD		
181843	1 ft 10 in x 1 ft 8 in x 2.28 in	3,000 x 1	\$1,695.00
181844	1 ft 10 in x 1 ft 8 in x 2.28 in	6,500 x 2	\$1,695.00
181845	1 ft 10 in x 1 ft 8 in x 2.28 in	13,000 x 5	\$1,695.00
181846	1 ft 10 in x 1 ft 8 in x 2.28 in	22,000 x 10	\$1,825.00
181847	1 ft 10 in x 1 ft 8 in x 2.28 in	33,000 x 10	\$1,825.00
Load Ranger RF-	WD		
181848	2 ft 6 in x 1 ft 10 in x 2.28 in	13,000 x 5	\$2,100.00
181849	2 ft 6 in x 1 ft 10 in x 2.28 in	22,000 x 10	\$2,100.00
181850	2 ft 6 in x 1 ft 10 in x 2.28 in	33,000 x 10	\$2,100.00
Load Ranger RF-	XWD		
181851	3 ft 1 in x 2 ft x 2.28 in	13,000 x 5	\$2,575.00
181852	3 ft 1 in x 2 ft x 2.28 in	22,000 x 10	\$2,575.00
181853	3 ft 1 in x 2 ft x 2.28 in	33,000 x 10	\$2,575.00
181854	3 ft 1 in x 2 ft x 2.28 in	44,000 x 20	\$2,575.00

Options/Accessories

Part #	Description	Price
181881	Aluminum Ramp for Load Ranger MD Models	\$245.00
181882	Aluminum Ramp for Load Ranger WD Models	\$275.00
181883	Aluminum Ramp for Load Ranger XWD Models	\$300.00