



**Features**

- Compact
- Lightweight
- Easy to Install
- Excellent Noise Reduction
- Protects Components from Contamination
- NPT and BSPT Threads Available

**Application**

The plastic silencer is designed to give excellent noise reduction with a minimum effect on air efficiency. The "Trimline" design allows for locating the silencer in the tightest places without extra plumbing or fittings. Fits directly into the exhaust port of most commercial valves. Open surface area of element allows for rapid discharge of air without undesirable back pressure.

Part Number		Thread Size	A (mm)	B (mm)	Maximum Flow (SCFM) 100 PSIG Inlet	Sound Pressure Level (dBA)	
NPT	BSPT					20 PSIG Inlet	100 PSIG Inlet
<b>AS-5</b>		M5	0.43 (11)	0.32 (8)	15	69	79
<b>ASN-6</b>	<b>AS-6</b>	1/8"	1.57 (40)	0.63 (16)	51	69	81
<b>ASN-8</b>	<b>AS-8</b>	1/4"	2.56 (65)	0.83 (21)	124	67	84
<b>ASN-10</b>	<b>AS-10</b>	3/8"	3.35 (85)	0.98 (25)	247	83	98
<b>ASN-15</b>	<b>AS-15</b>	1/2"	3.74 (95)	1.18 (30)	370	69	96

**Specifications**

**Pressure Rating**.....0 to 150 PSIG  
 (0 to 10 bar, 0 to 1034 kPa)  
**Temperature Rating** ..... 14°F to 140°F (-10°C to 60°C)  
**Body** .....Acetal (Plastic)  
**Element** ..... Polyethylene

**D**

- Tanks & Air Chucks
- Mufflers & Silencers
- Relief & Exhaust Valves
- Pressure Switches
- AirGuard Protection
- Drain Valves
- Safety Blow Guns