Summit Scale and Indicator Package

Floor Scale/Indicator Package



Package is configured, corner-trim, and calibrated for 5,000 divisions before shipping

Floor Scale and Indicator Package

Package includes Summit[®] 3000 floor scale, 120 PLUS digital weight indicator with tilt stand, 20 ft load cell cable with quick disconnect, configured and calibrated

Standard Features

Summit[®] 3000 Floor Scale

Summit

- · Four NTEP Certified alloy steel-shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2-20NF) located in the center of the deck for easy lifting
- · 20ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions

120 Digital Weight Indicator

- Large 0.8 in (20.3 mm) light emitting diode (LED) display
- Five-button operation
- Full front panel digital calibration and configuration

120 PLUS Digital Weight Indicator

- Large 0.8 in backlit liquid crystal display (LCD)
- 115 or 230 VAC wall adapter with rechargeable battery

Specifications

Summit 3000 Floor Scale

End Load Capacity:

100% full scale at 5,000 lb (2,500 kg) 80% full scale at 10,000 lb (5,000 kg)

Cable Length:

20 ft (6.1 m) (for connecting junction box to indicator) **Warranty:**

Summit 3000 weldment and load cells two years, all other components one year

Approvals:

NTEP CC 92-001A9, Class III 5,000 d Measurement Canada AM-5530, Class III 5,000 d (2,500 kg, 5,000 kg) 2,000 d (1,000 kg)

120/120 Plus Digital Weight Indicator

Power:

120/120 Plus:

Line voltages: 115 or 230 VAC Frequency: 50 or 60 Hz 120 Plus: (estimated battery life) 60 hours with 1 x 350 Ω 40 hours with 4 x 350 Ω

40 hours with 4 x 350 Ω Charge time 8 hours

Operating Temperature:

Legal: 14° F to 104° F (-10° C to 40° C) Industrial: 14° F to 122° F (-10° C to 50° C)

Rating/Material:

Enclosure: heavy gauge ABS

Warranty:

One-year limited warranty

120 Approvals:

NTEP CC 03-059, Class III/IIIL 6,000 d Measurement Canada AM-5517, Class III/IIIHD 6,000 d OIML TC7028 T 5692, 5,000 d CE marked

120 Plus Approvals:

NTEP CC 03-059, Class III/IIIL 6,000 d Measurement Canada AM 5517 OIML TC 7626, T5692 5,000 d Class III/IIIHD 6,000 d



Part Number/Price

Part #	Size (W x L x H)	Capacity	Est. Weight	Price
Floor Scale	e and Indicator Package (Single Scale)			
Package incl	ludes Summit® 3000 floor scale, 120/120 PLUS digital weig	ht indicator with tilt stand, 20 ft load ce	Il cable with quick disconnect,	
configured a	nd calibrated			
115 VAC (12				
78772	4ft x 4ft x 3.625 in	5,000 lb x 1 lb	315lb	\$1,475.00
78773	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	\$1,475.00
115 VAC (12			0.45.1	
106913	4ft x 4ft x 3.625 in	5,000 lb x 1 lb	315 lb	\$1,625.00
106914	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	\$1,625.00
230 VAC (12 78780	4 ft x 4 ft x 3.625 in	5.000 lb x 1 lb	315lb	¢1.475.00
78780	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb 10,000 lb x 2 lb	315lb	\$1,475.00
230 VAC (12			31510	\$1,475.00
230 VAC (12 106915	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315lb	\$1.625.00
106915	4ft x 4ft x 3.625 in	10,000 lb x 2 lb	315lb	\$1,625.00
	nadian Weights and Measures (120)	10,000 10 x 2 10	31310	\$1,025.00
78776	4ft x 4ft x 3.625 in	2,500 lb x 0.5 kg	315 lb	\$1,475.00
78777	4ft x 4ft x 3.625 in	5,000 lb x 1 kg	315 lb	\$1,475.00
-	nadian Weights and Measures (120 PLUS)	0,000 lb X 1 kg	01015	¢1,110.00
106917	4ft x 4ft x 3.625 in	2,500 lb x 0.5 kg	315 lb	\$1,625.00
106918	4 ft x 4 ft x 3.625 in	5,000 lb x 1 kg	315 lb	\$1,625.00
Floor Scale	e and Indicator Package (Five-scale Package)			
Packages in	clude five Summit® 3000 floor scales, five 120/120 Plus dic	jital weight indicators with tilt stands, fi	ve 20 ft load cell cables	
	isconnect, configured and calibrated			
115 VAC (12				
78774	4ft x 4ft x 3.625 in	5,000 lb x 1 lb	1,665 lb	\$7,075.00
78775	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1,665 lb	\$7,075.00
115 VAC (12 106929			1.005 lb	¢7,005,00
106929	4ft x 4ft x 3.625 in	5,000 lb x 1 lb	1,665 lb	\$7,825.00
230 VAC (12	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1,665 lb	\$7,825.00
230 VAC (12 78782	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1.665 lb	\$7.075.00
78783	4ft x 4ft x 3.625 in	10.000 lb x 2 lb	1.665 lb	\$7,075.00
230 VAC (12			U	φι,σιο.ου
230 VAG (12 106931	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1,665 lb	\$7,825.00
106932	4ft x 4ft x 3.625 in	10.000 lb x 2 lb	1,665 lb	\$7,825.00
	nadian Weights and Measures (120)			¢1,020.00
78778	4ft x 4ft x 3.625 in	2,500 kg x 0.5 kg	1.665 lb	\$7,075.00
78779	4ft x 4ft x 3.625 in	5,000 kg x 1 kg	1,665 lb	\$7,075.00
	nadian Weights and Measures (120 Plus)			, ,
106933	4ft x 4ft x 3.625 in	2,500 kg x 0.5 kg	1,665 lb	\$7,825.00
106934	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	1,665 lb	\$7,825.00

Options/Accessories

Part #	Description	Price		
Summit® 3000 Floor Scale				
N/A	Access ramps, pit frames, bumper guards and portability frames available	See end of section for details		
75819	Floor anchor plates, mild steel (set of two)	\$25.00		
76012	Additional operating manual	\$10.00		
120 Digital Weight Indicator				
77925	Revolution® scale software*	\$35.00		
103636	Power supply, 120 Plus wall adapter, 115/230 VAC, 5 VDC	\$40.00		
76699	Additional operating manual	\$31.00		

RICELAKE