Rice Lake RS-130/RS-160

Battery-Operated Price Computing Scales



Part Number/Price

| Part # | Model | Capacity | Weight | Price |
|--------|--------------|--|--------|----------|
| 167941 | RS-130 Bench | 30 lb x 0.01 lb 15 kg x 0.005 kg 480 oz x 0.2 oz | 12 lb | \$354.00 |
| 168100 | RS-130 Pole | 30 lb x 0.01 lb 15 kg x 0.005 kg 480 oz x 0.2 oz | 13 lb | \$365.00 |
| 167942 | RS-160 Bench | 60 lb x 0.02 lb 30 kg x 0.01 kg 960 oz x 0.5 oz | 12lb | \$364.00 |
| 168101 | RS-160 Pole | 60 lb x 0.02 lb 30 kg x 0.01 kg 960 oz x 0.5 oz | 13 lb | \$375.00 |


NOTE: Buy quantity of 5 and get a 50% discount

Options/Accessories

| Part # | Description | Price |
|--------|--|---------|
| 169634 | Additional operating manual | \$15.00 |
| 169635 | Additional calibration instructions | \$5.00 |
| 85711 | Additional in-use cover | \$5.25 |
| 47976 | Fish platter, (W x D) 9.5 x 13.5 in | \$95.00 |
| 47977 | Produce platter, (W x D) 9.5 x 13.5 in | \$75.00 |
| 85710 | Replacement rechargeable battery, 6V | \$21.00 |

| Dimensions: Bench |
|--|
| Unit |
| 11.8 in x 13.0 in x 4.7 in (300 mm x 330 mm x 120 mm) |
| Stainless Steel Platter |
| 11.8 in x 9.5 in (300 mm x 240 mm) |

| 11.0111 x 3.3111 (300111111 x 240111111) | | |
|--|--|--|
| | | |
| Dimensions: Pole | | |
| Unit | | |
| 11.8 in x 13.0 in x 4.7 in | | |
| (300 mm x 330 mm x 120 mm) | | |
| | | |
| Stainless Steel Platter | | |
| 11.8 in x 9.5 in (300 mm x 240 mm) | | |
| Head | | |
| 11 in x 3.1 in (280 mm x 78 mm) | | |
| | | |



Standard Features

- Toggle between lb/kg/oz*
- Nine PLU keys for direct price lookups
- · Green backlight
- Cash back calculation
- · Large stainless steel platter
- Easy-to-read displays
- In-use cover
- Battery charge indicator
- · Internal sealed battery included
- · NTEP Certified, Legal for Trade

Specifications

Capacity/Graduations:

RS-130: 30 lb x 0.01 lb 15 kg x 0.005 kg 480 oz x 0.2 oz

RS-160:

60 lb x 0.02 lb 30 kg x 0.01 kg 960 oz x 0.5 oz

Display Items:

Weight: Five-digits Unit price: Five-digits Total price: Six-digits

Accuracy:

1/3,000

Display:

Backlit LCD, 0.453 in (11.5 mm) character height

Power Source:

DC 6V/25 mA rechargeable battery with AC adaptor included AC 115V/0.1A (max) (100+ hours battery life, 8-10 hours to recharge)

Weight:

10 lb (4.5 kg)

Preset Key:

Nine direct price lookups

Dimensions:

Platter: (W x D) 11.8 x 9.5 in Overall: (W x D x H) 12.3 x 13.0 x 4.7 in

Operating Temperature:

32°F to 104°F (0°C to 40°C)


Classification:

NTEP CC 04-067, Class III 3000d

*Not Measurement Canada Approved

Warranty:

One-year limited warranty



950

Unit with Pole

11.8 in x 9.5 in x 16.1 in (300 mm x 240 mm x 410 mm)