



Standard Features:

- Fiberglass Reinforced Polyester (FRP), NEMA Type 4X enclosure
- · Strain relief cable fittings
- Individual cell signal disconnect switches
- Number of cells: 2 or 4 single cells (even number of cells only)
- Expansion port

Part Number/Price

	-	
Part#	Description	Price
21169	EL304A signal trim four-channel junction box	\$295.00
21301	Board only	\$215.00
165275	Enclosure only (includes cord grip)	\$145.00

Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.

Specifications:

Cable Fittings:

- 4 nylon cable strain reliefs 0.079 in-0.236 in (2.0 mm-6.0 mm)
- 2 nylon cable strain reliefs 0.236 in-0.354 in (6.0 mm-9.0 mm)

Connectors:

Electrovert 0.197 in (5.0 mm) miniature screw terminals. Maximum wire size #14 AWG

Trimming:

- Individual cell and section, signal trim
- **Potentiometers:**
- 100K ohm, 25-turn cermet

Enclosure:

- FRP NEMA Type 4X, 40 PSI washdown **Circuit Board:**
- 5.5 in x 4 in (139.7 mm x 101.6 mm) with anti-fungal coating

Warranty:

One-year limited warranty

Applications:

5.50″

EXC

CELL #2

DAA

CELL #1

.

- Livestock scales
- Tank and vessel weighing
- Corner and/or section trim applications

SHLD +SIG +EXC

SECTION #2

I

CELL #4

đ 1868

00000 00000

F -SIG +SIG EXC EXC

00000 00000

EXC

CELL #3

SHLD

+SIG

SIG

+SEN

+EXC

SEN

EXC

INDICATOR

10.01

REV

COMPONENTS

EL304A

