

## Specifications

**Load Cell, NTEP Certified:**

Aluminum, environmentally sealed

**Output Impedance:**

350 Ω

**Maximum Overload:**

200%

**Overload Protection:**

Five-point, independently adjusted

**Cable Length:**

10 ft (3 m)

**Compensated Temperature Range:**

14° F to 104° F (-10° C to 40° C)

**Warranty:**

Two-year limited warranty

**Approvals:**

NTEP CC 06-010, Class III 5,000 d

Measurement Canada AM-5625, Class III 5,000 d



*Ideal for Aviation Weighing. A complete system can be sold with the Tracer® AV. Reference Aviation section for specifications*

## Standard Features

- Heavy-duty designed mild steel base construction with 304 stainless steel cover
- Polyurethane rubber leveling feet with stainless steel stems

## APPROVALS



Measurement  
Canada  
Approved



## Part Number/Price

Part #	Capacity	Platform Dimensions (L x W x H)	Est. Weight	Price
93414	250 lb (125 kg)	30 x 30 x 8.75 in	300 lb	\$1,675.00
93415	500 lb (225 kg)	30 x 30 x 8.75 in	300 lb	\$1,675.00
93416	250 lb (125 kg)	36 x 36 x 8.75 in	330 lb	\$2,035.00
93417	500 lb (225 kg)	36 x 36 x 8.75 in	330 lb	\$2,035.00

*Consult factory for modifications for airport baggage scales.*

