

# ISOBAR®

AC Transient Protector



## Specifications

- Clamp Voltage:**  
140V rms
- Peak Surge Current:**  
13,000 amps
- Clamping Time:**  
Less than five nanoseconds
- Input Voltage:**  
120 VAC
- Maximum Current:**  
15 amps
- Maximum Power:**  
1875 watts
- Noise Suppression:**  
Frequency attenuation  
50 KHz>20 db  
150 KHz>40 db  
1 MHz>80 db  
>6 MHz>30 db
- Dimensions:**  
(W x H x D) 6.15 x 3.56 x 2.48 in  
(156.2 x 90.4 x 63.0 mm)
- Weight:**  
Approximately 2 lb (0.91 kg)

## Standard Features

- Four outlets
- Six-foot cord with grounded three-prong plug
- Lighted on/off switch
- Circuit breaker protected
- Multiple filter design prevents the different components of your system from interfering with each other
- UL1449 listed at 330 volts
- Exclusive isolated filter banks prevent equipment interaction
- ISOBAR's cascade circuitry allows you to choose more protection for your most sensitive equipment and a lesser degree of protection for equipment with more tolerance

## Part Number/Price

Part #	Description	Weight	Price
21146	ISOBAR® AC four-outlet transient protector, 115 VAC	2 lb	\$110.00
36663	ISOBAR 230 VAC Euro	3 lb	\$155.00

