

Part Number/Price

Part #	Description	Price
91233	320IS intrinsically-safe digital weight indicator five-button keypad with battery pack and charger & tilt stand	\$1,827.00
91234	320IS intrinsically-safe digital weight indicator five-button with A/C power supply	\$1,827.00
177500	320IS indicator only	\$1,095.00

Options/Accessories

Part #	Description	Price
174049	Power supply, IS-EPS-100-240 VAC	\$845.00
179142	DC extension cable 10 ft	\$100.00
179143	DC extension cable 25 ft	\$125.00
179144	DC extension cable 50 ft	\$150.00
179145	DC extension cable 75 ft	\$200.00
179146	DC extension cable 100 ft	\$225.00
72725	IS-6 V battery option with cable adapter	\$545.00
74001	Battery charger, 115 VAC	\$149.00
74002	Battery charger, 230 VAC	\$535.00
80869	Fuse, 1.25A, 250 V TR5 time-lag (replacement part for the I/O module)	\$2.50
72726	Tilt stand (required for battery model)	\$57.00
89239*	I/O module, stainless steel NEMA Type 4 enclosure, safe area option (requires fiber optic cable, AC power required)	\$1,295.00
83388	Timer relay kit includes din rail, timer relay for latching and mount	\$370.00
74612	Installation manual	\$35.00
78076	I/O module manual	\$30.00
Hazardous Environment Cable		
32817	EL147IS hazardous environment cable	\$2.85/ft
72241	Hazardous environment 3 conductor	\$2.25/ft
78026	Fiber optic, duplex cable 100 ft	\$135.00
78027	Fiber optic, duplex cable 200 ft	\$270.00

* Includes relays

I/O module required for anything besides basic weighing

Dimensions			
Without Battery			
A	8.56 in (217.4 mm)	D	2.64 in (67.1 mm)
B	6.00 in (152.4 mm)	E	3.75 in (95.2 mm)
C	9.50 in (241.3 mm)		
With Optional Battery and Tilt Stand			
F	11.56 in (293.6 mm)	G	4.75 in (120.7 mm)
Optional I/O Module			
12.90 in x 11.63 in x 6.25 in (327.7 mm x 295.4 mm x 158.8 mm)			
Optional Power Supply			
7.00 in x 5.13 in x 3.125 in (177.8 mm x 130.0 mm x 79.375 mm)			

