

PSE-800-M

Manual Reset LWCO for Steam Boilers

The Series PSE-800-M is a new addition to the McDonnell & Miller probe type low water cut-off group of products. These controls are used as the secondary LWCO on steam boilers and can also be used as the primary LWCO on hot water heating boilers.

Features and Benefits Include

Lockout Delay

If a low water condition occurs (water off probe), the burner will turn off and the red LED will begin to blink. If the water level is not restored to a level above the probe with-in 60 seconds, the control will lock out. The reset button will need to be pressed when water level is restored to a level above the probe.

CSD-1 Code Compliance

If the control is in a low water condition (water off probe) when there is an interruption of power, the control will remain in a low water condition when power is restored. The reset button will have to be pressed when the water level is restored to a level above the probe.

Power Interruption

If there is a loss of power, the control will automatically reset if there was water on the probe before the loss of power AND there is water on the probe when the power is restored.

Self-cleaning Probe

This is available only on McDonnell & Miller probe type controls which reduces probe maintenance to once every five years instead of annually.

Test Button

Standard on all controls to allow the control to be tested without draining the boiler or system.

'Green' Power On & 'Red' LWCO LED's

Standard on all units to give visual indication that the unit is powered up and when a low water condition is detected.



McDonnell & Miller
a xylem brand

Series PSE-800-M Manual Reset LWCO

Competitive Cross Reference

	McDonnell & Miller	Hydrolevel	TACO	Honeywell
PSE-801-M-120	PS-801-M-120	550, 750	LFM1203S-1 LTM1203S-1	RW700B
PSE-801-M-U-120	PS-801-M-U-120	550P		
PSE-802-M-24	PS-802-M-24	500, 700	LFM0243S-1 LTM0243S-1	
PSE-802-M-U-24	PS-802-M-U-24			

Ordering Information

Model Number	Part Number	Description	Weight Lbs. (kg)
PSE-801-M-120	153601	120V Manual Reset w/standard probe	2.7 (1.2)
PSE-801-M-U-120	153603	120V Manual Reset w/ext. barrel probe ("U")	2.7 (1.2)
PSE-802-M-24	153602	24V Manual Reset w/standard probe	2.7 (1.2)
PSE-802-M-U-24	153604	24V Manual Reset w/ext. barrel probe ("U")	2.7 (1.2)



Xylem Inc.
8200 N. Austin Avenue
Morton Grove, Illinois 60053
Phone: (847) 966-3700
Fax: (847) 965-8379
www.mcdonnellmiller.com

McDonnell & Miller is a trademark of Xylem Inc. or one of its subsidiaries.
© 2014 Xylem, Inc. MPF-001A June 2014