

HORIZONTAL

AUTOTIE LINE

COMPACTION. AUTOMATION. PRODUCTION.

HEAVY DUTY PERFORMANCE

In the high grade paper and OCC recycling environments, your horizontal baler can make the difference between marginal production and great success. The horizontal autotie balers from Harris offer innovative features designed for optimum performance and increased durability.

Performance-based features include a unique design which maximizes baling speed and thru-put, an optional lid feature to increase tonnage capacities without increasing horsepower requirements, and a large hopper opening to accommodate conveyor-fed operations. The highest level of process customization, diagnostics, and production status motoring is made simple through the use of programmable logic controllers. The need for a baler operator has been virtually eliminated. The hydraulically-actuated wire tying

capability ensures simplicity, ease of adjustment, and long component life.

Let us help you solve your recycling problems. Call today to learn more about the complete line of Horizontal Auto-Tie Balers from Harris.

PERFORMANCE-BASED FEATURES

- Replaceable Wear Components
- TEFC High Efficiency Motor
- AR400 Abrasion Resistant Alloy Steel Shear Blades
- Adjustable Shear Bar
- Automatic Cycle
- Meets or Exceeds All Current ANSI Z 245.5 Safety Standards





HORIZONTAL AUTO-TIE BALER SPECIFICATIONS

| | MODEL | AT-736 20/30 | AT-752 20/50 | AT-864 30/50/75 | AT-872 30/50/75 | AT-885 30/50/75 |
|-------------|---|---|--|--|--|--|
| | Main Cylinder | 7" Bore 178 mm | 7" Bore 178 mm | 8" Bore 203 mm | 8" Bore 203 mm | 8" Bore 203 mm |
| Į | System Pressure | 3000 PSI 207 Bar | 3000 PSI 207 Bar | 3000 PSI 207 Bar | 3000 PSI 207 Bar | 3000 PSI 207 Bar |
| HYDRAULIC | Total Force | 115,400 LB | 115,400 LB | 150,800 LB | 150,800 LB | 150,800 LB |
| | Ram Face Pressure | 93 PSI 6.4 Bar | 63 PSI 4.3 Bar | 83 PSI 5.7 Bar | 74 PSI 5.1 Bar | 74 PSI 5.1 Bar |
| | Tension Cylinder | 6" Bore 152 mm | 6" Bore 152 mm | 6" Bore 152 mm | 6" Bore 152 mm | 6" Bore 152 mm |
| ELECTRICAL | Main Motor | 20/50 HP 15/37 kW | 20/50 HP 15/37 kW | 30/50/75 HP 22/37/56 kW | 30/50/75 HP 22/37/56 kW | 30/50/75 HP 22/37/56 kW |
| | Cooler Fan Motor | 2/3 HP 1.5/2.25 kW | 2/3 HP 1.5/2.25 kW | 3 / 5 HP 2.25 / 3.75 kW | 3/5 HP 2.25/3.75 kW | 3/5 HP 2.25/3.75 kW |
| STRUCTURAL | Length Overall | 26 ft 5 in 8 meter | 29 ft 8 in 9 meter | 31 ft 8 in 9.6 meter | 31 ft 8 in 9.6 meter | 33 ft 8 in 10.3 meter |
| | Width Overall | 14 ft 10 in 4.5 meter | 14 ft 10 in 4.5 meter | 14 ft 10 in 4.5 meter | 15 ft 4 in 4.7 meter | 15 ft 4 in 4.7 meter |
| | Charge Hopper Height | 92 in 2.3 meter | 96 in 2.4 meter | 96 in 2.4 meter | 96 in 2.4 meter | 96 in 2.4 meter |
| | Charge Box Opening | 27 in W x 50 in L 686 mm W x 1270 mm L | 41 in W x 50 in L 1041 mm W x 1270 mm L | 41 in W x 60 in L 1041 mm W x 1524 mm L | 46 in W x 60 in L 1168 mm W x 1524 mm L | 46 in W x 72 in L 1168 mm W x 1829 mm L |
| | Machine Weight - Tons | 13 | 13 | 17 | 16.1 | 16 |
| PERFORMANCE | 29 in (737 mm) Wide x 43 in (1092 mm) High x Variable Length (Model AT-736) 43 in (1092 mm) Wide x 43 in (1092 mm) High x Variable Length (Models AT-752 & AT 864) 48 in (1219 mm) Wide x 43 in (1092 mm) High x Variable Length (Models AT-872 & AT-885) | | | | | |
| | Bale Weight OCC | Up to 1500 LB 681 KG | Up to 1525 LB 748 KG | Up to 1650 LB 816 KG | Up to 1800 LB 816 KG | Up to 1800 LB 816 KG |
| | Bale Volume Cubic Feet - 62" Length | 45 cu ft | 66 cu ft | 66 cu ft | 74 cu ft | 74 cu ft |
| | Cycle Time Seconds (No Load) | 30 / 13 sec | 20/9 sec | 19 / 14 / 10 sec | 19 / 14 / 10 sec | 22 / 14 / 11 sec |

STANDARD FEATURES:

- Programmable Logic Controller
- Hopper Access Door w/Safety Interlock
- Oil Cooler (Air over Oil) System 30 HP and above
- Bale Runout Table (6 ft long)
- TEFC Motors

AVAILABLE OPTIONS:

- Oil Heater
- Factory Start Up
- Conveyor Controls

As part of our continuing product improvement and quality assurance programs, specifications are subject to change without notice and without incurring responsibility for units previously sold.



HARRIS EQUIPMENT-CORDELE 315 W. 12TH AVE CORDELE, GA 31015 800.468.5657 229.273.2500 HARRIS EQUIPMENT-BAXLEY 340 JEKYLL RD BAXLEY, GA 31513 800.447.3526 912.367.4661 HARRIS EQUIPMENT UNITED KINGDOM OFFICE
UNIT D2 FORMAL INDUSTRIAL PARK
NORTHWAY LANE
TEWKESBURY GLOS GL20 8GY
+44 (0) 1684-254980
info.europe@harrisequip.com

