

HURST 10,000 PSI RESCUE PRODUCTS CATALOG

¹⁷ **HURST** HP RAMS



¹⁸ **HURST** R 430 RAM AND ACCESSORIES



World's First Triple Stage Ram

The world's first triple stage ram, the **R 430**, is capable of carrying out the heaviest rescue operations with push capacity up to 30 U.S. tons in the first stage and 14 U.S. tons in the second stage.

Through a telescopic design, its retracted length of only 18.7 inches can be extended to 50.98 inches in three stages. This long working range considerably reduces extrication times by consolidating steps normally required in a sequence of several traditional rams.

Compact and lightweight, with a high resistance against lateral load, the R 430 is adept at moving obstacles, lifting loads and creating openings and stabilization in traffic, railroad, aircraft and marine rescues, as well as building and disaster recovery. Claws on the top and base provide a firm grip on flat and angled surfaces.

SPECIFICATIONS

RAM	R 430	247C023
PART #	274070000	
LENGTH RETRACTED (IN/MM)	18.7/475	
WIDTH (IN/MM)	4.41/112	100 20
DEPTH (IN/MM)	8.70/221	
WEIGHT (LBS/KGS)	39/17.7	
LENGTH EXTENDED (IN/MM)	51/1295	
PUSHING FORCE MAX. (LBS/kN)	Piston 1: 60,474/269	LRS 120
	Piston 2: 30,124/134	
	Piston 3: 8,768/39	
STROKE (IN/MM)	Piston 1: 11.6/295	
	Piston 2: 11/280	
	Piston 3: 9.65/245	
	Overall: 32.3/820	



¹⁹ **HURST** R 420, R 422, R 424 AND ACCESSORIES



World's First Complete Range of Telescopic Rams

The world's first complete range of telescopic rams, the **R 420**, **R 422** and **R 424** can lift up to 30 U.S. tons in first stage and 14 U.S. tons in the second stage. These lightweight but powerful telescopic rams combine minimal retracted height with enormous lifting stroke, reaching lifting heights of two standard rams with one stroke. Claws on the top and base provide a firm grip on nearly any surface.







SPECIFICATIONS

RAMS	R 420	R 422	R 424
PART #	274040000	274050000	274060000
LENGTH RETRACTED (IN/MM)	18.9/480	21.7/550	24.6/625
WIDTH (IN/MM)	4.41/112	4.41/112	4.41/112
DEPTH (IN/MM)	8.70/221	8.70/221	8.7/221
WEIGHT (LBS/KGS)	37/16.8	41.4/18.8	46.3/21
LENGTH EXTENDED (IN/MM)	41.5/1,055	49.4/1,255	59.1/1,500
PUSHING FORCE MAX. (LBS/kN)	Piston 1: 60,474/269	Piston 1: 60,474/269	Piston 1: 60,474/269
	Piston 2: 30,124/134	Piston 2: 30,124/134	Piston 2: 30,124/134
STROKE (IN/MM)	Piston 1: 11.6/295	Piston 1: 14.4/365	Piston 1: 17.5/445
	Piston 2: 11/280	Piston 2: 13.4/340	Piston 2: 16.9/430
	Overall: 22.6/575	Overall: 27.8/705	Overall: 34.5/875

²⁰ **HURST** R 410, R 412, R 414 AND ACCESSORIES



The Hurst Jaws of Life[®] **R 410**, **R 412** and **R 414** are our standard traditional ram series in gradual sizes. The smaller ram creates the incremental opening for the next size.







SPECIFICATIONS

RAMS	R 410	R 412	R 414
PART #	274110000	274120000	274130000
LENGTH RETRACTED (IN/MM)	17.7/450	26.8/680	35.4/900
WIDTH (IN/MM)	3.74/95	3.74/95	3.74/95
DEPTH (IN/MM)	6.85/174	6.85/174	6.85/174
WEIGHT (LBS/KGS)	28.7/13	39.5/17.9	53.4/24.2
LENGTH EXTENDED (IN/MM)	29.5/750	46.5/1180	63/1600
PUSHING FORCE MAX. (LBS/kN)	30,799/137	30,799/137	27,876/124
STROKE (IN/MM)	11.8/300	19.7/500	27.6/700