

**JCB North American Headquarters** 

Savannah. 2000 Bamford Blvd., Savannah, Georgia, 31322 Tel: (912) 447-2000 Download the very latest information on this product range at jcbna.com

JCB inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB inc. All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependant upon the exact specification of machine. They should not therefore be relied upon in relation to suitability for a particular application. Guidance and advice should always be sought from your JCB Dealer. JCB reserves the right to change specifications without notice Illustrations and specifications shown may include optional equipment and accessories. The JCB logs is a registered trademark of J C Bamford Excavators Ltd.







# ONE TOUGH RAIL MACHINE

THE WORLD'S BEST SELLING RANGE OF BACKHOE LOADERS IS READY TO TAKE ON THE RAIL INDUSTRY. FEATURING THE STRONGEST SWING FORCES AVAILABLE. JCB BACKHOE LOADERS ARE THE PREFERRED MACHINE FOR CONTRACTORS AND FLEET OWNERS ALIKE

#### **Durability**

JCB backhoe loaders are built to withstand the harshest of applications and are perfect for rail contractors. The stress relieved boom goes through a heating process which strengthens the structures giving JCB loaders less weight in the back without sacrificing its high quality.

#### **Built for Rail**

Featuring the largest swing cylinders in the industry, JCB backhoes deliver 18,000 lbs of swing torque, making our machines the perfect tool for replacing railroad ties.


### **Extradig Design**


The innerbox extending dipper design extends less weight resulting in better stability compared to competitive models. The wear pads are adjustable in the field, making it perfect for tough rail applications.

## Rail Ready

4 A number of compatible high rail options are available, including a rear rail dolly and flip over rail runners, ensuring productive, safe rail operation and travel.









18,000lbs of swing torque, and 2" thick swing frame ensure robust strength when operating laterally.

linkage provides class-leading visibility and aids with material retention. AutoSmoothRide is especially useful when using forks to carry ties.

#### **Ease of Operation**

The pilot controls on our 3CX-Supers are seat mounted, allowing operators to use both ends of the machine without turning around. In addition, a floor-toceiling rear window provides excellent visibility to the excavator bucket for precision work around rail road tracks.

### **Versatility**

a variety of rail specific attachments including: cribbing buckets, thumbs, rail riding systems and a Hand Held Tool Circuit, especially useful when using a hammer to secure replaced ties.

E LiveLink enabled machines provide











■ The standard parallel front loader



Z All 3CX-Supers are available with

#### **Automatic Reporting**

reports on fuel usage, machine operation, location and even service alerts direct to your desktop or phone, enabling effective management and security of your machines.