

FIELD PROVEN RELIABILITY

THE RIGHT TOOLS FOR THE MOST EXTREME JOBS.

For over 65 years, Elliott Equipment Company has manufactured lifting and personnel handling equipment that's built to last. We start with a full length subframe to give you stable performance and help your chassis last longer. We utilize oversized turrets and bearings for more rigidity and lifting capacity. Our controls incorporate cutting edge hydraulic valves and fully hydraulic controls that work day in and day out. Every Elliott comes with peace of mind knowing that your investment is backed by the best warranty in the business.



45127 BoomTruck

PICK WITH CONFIDENCE

Elliott's boom trucks offer best in class lifting capabilities. With single line pulls starting at 9,600 lbs on our smallest cranes, Elliott boom trucks make it easier to perform effectively on the job site.

Every crane model undergoes testing to verify compliance with the industry's most rigorous stability and structural standards. Plus, each machine incorporates a range of safety features including a computerized LMI, hard-wired A2B switch and more.



1870 BoomTruck



C40F HiReach



1881TM Tractor



1860TM Tractor



Auxiliary Winch

WHY ELLIOTT?

Faster jobs, increased safety, and maximized equipment life and uptime make Elliott's BoomTruck and HiReach material handling aerial work platforms some of the most innovative and feature-packed products on the market. Plus, each machine is built specifically for you and your needs. Boost your productivity and jobsite performance with an Elliott.

Built for You.

BoomTruck™

OIL & GAS INDUSTRY MODELS

MODEL	LIFTING CAPACITY	BOOM LENGTH	TIP HEIGHT	BOOM SECTIONS	SINGLE LINE PULL	OUTRIGGER SPREAD
1047	10 Tons	47'	57'	3	9,600 lbs	17' 7"
1870	18 Tons	70'	80'	3	9,600 lbs	20' 10"
1881TM	18 Tons	81'	91'	5	9,600 lbs	20' 10"
26105	26 Tons	105'	117'	4	9,060 lbs	20' 10"
36127	36 Tons	127'	137'	5	9,060 lbs	21' 2"
40142	40 Tons	142'	152'	5	10,000 lbs	26' 2"
45127	45 Tons	127'	137'	5	10,000 lbs	26' 2"

HiReach™

MODEL	WORKING HEIGHT	SIDE REACH	PLATFORM CAPACITY	LIFTING CAPACITY	PLATFORM SIZE	GVWR MIN.
G40F	45'	30'	1,000 lbs	1,000 lbs	40" x 60"	25,999 lbs
C40F	45'	30'	1,000 lbs	14,000 lbs	40" x 60"	33,000 lbs
V60F	63'	38'	500 lbs	500 lbs	30" x 40"	19,500 lbs

FEATURES & BENEFITS

- BoomTruck Turret Mounted Further Back on Chassis for Improved Pick at Tight Radius
- HiReach Oversized High-Capacity Work Platform to Carry More Workers and Tools
- HiReach Material Handling in the Work Platform and on the Boom for a Two-In-One Solution
- Steel BoomTruck Crane Cab with Flat Glass for Excellent Reliability and Low Maintenance Costs
- BoomTruck Winch Single Line Pulls from 9,060 to 10,000 lbs for More Lifting With Less Rope
- Multiple BoomTruck Boom Lengths for More Job-Specific Versatility
- Lifetime Structural Warranty for Added Peace of Mind

OIL & GAS OPTIONS

- BoomTruck Dual Winch Package with Auxiliary Sheave Case on Boom Tip
- BoomTruck Hydraulic or Electric/Hydraulic Controls
- BoomTruck Crane Cab AM/FM/CD Player and Air Conditioning System
- Custom Boom Rests for Bed-Mounted Racks or Trailer Connections
- Custom Outriggers for Offroad Conditions for Extra Ground Penetration
- Extreme Climate Packages for Improved Performance and Equipment Protection
- BoomTruck Tractor Mount Options for Most Models

BUILT FOR YOU

- Choose From a Wide Selection of Flatbeds, Service Bodies, Boxes and Bumpers
- Select From a Variety of Boom Truck Mounting Configurations
- Choose a Truck With the Right Dependability, Engine and Transmission for the Job
- Add Custom Options to Make Your Machine the Perfect Fit for Your Business

CONTACT US

Visit www.elliotequip.com to find a dealer in your area for pricing, availability, rentals, financing and more. Contact Elliott directly at sales@elliotequip.com or (402) 592-4500.




AUXILIARY WINCH PACKAGE



TRACTOR MOUNT BOOMTRUCKS



ELLIOTT DYNASMOOTH CONTROLS



TURNKEY CUSTOM SOLUTIONS



DELUXE OPERATOR CAB



HI REACH PLATFORM & JIB WINCH



CUSTOM FLATBEDS



SPECIALIZED TRUCK CONFIGURATIONS