ORWAK COMPACT 3115

THE ORWAK COMPACT 3115 is ideal for small volumes of plastic foil, but is also designed for cardboard compaction. A material selector makes the choice easy! The cross-binding function gives a tight grip of the bale and is helpful for compaction of soft plastic or small pieces of material.

Cross-binding



Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO_2 emissions. Sorting at source yields a higher quality of waste material for recycling.



Why Orwak Compact?

- Strong compaction on the spot! Requires little space, yet provides effective volume reduction
- + Easy-to-handle light weight bales
- The best choice for small to medium size volumes of cardboard and plastic



COMPACT

Complies to

ORWAK COMPACT

EN 16500 Safety standard

www.orwak.com

ORWAK COMPACT 3115

Compact and versatile balerfits where you need it!

PREPARED FOR CROSS-BINDING

3115 is designed for cross-binding, a function that helps secure the bales and one that is particularly useful when compacting small pieces of material.

AUTOSTART FOR EFFICIENT COMPACTION

An autostart function allows the baler to start compacting the material as soon as you close the door.

MATERIAL SELECTOR

A material selector makes the choice between compacting cardboard and plastic easy.




Transparent covers for strap reels

Modern design

Pocket for

operating



Adjustable bale size

ORWAK COMPACT 3115 IS OPTIMIZED FOR:

PAPER

- + Cardboard
- + Shredded paper
- + Paper sacks

OTHER METALS

+ Steel straps

OTHER PLASTICS

+ Plastic straps

PLASTIC FOIL

+ Shrink film

+ Plastic bags

ADJUSTABLE BALE SIZE

The cardboard bales weigh up to 60 kg and 3115 offers three different sizes of bale height for more options in waste management.


SILENT OPERATION CONTRIBUTES TO A BETTER WORKING ENVIRONMENT

Thanks to a silent type of hydraulics, the sound emission is low, which contributes to improving the working environment for the employees and is an important feature if the baler is installed close to customers.

Complies with the EN 16500:2014 safety requirement standard for vertical balers

DIMENSIONS & SPECIFICATIONS

DIMENSIONS		C D E						
A	В	с	D	E				
1990 mm	940 mm	790 mm	1535 mm	650 mm				



Weight (machine) Total: 380 kg

TECHNICAL SPECIFICATIONS

LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER					
Width: 800 mm Height: 460 mm	33 secs	HP 6 ton, 60 kN LP 4 ton, 40 kN	Width: 800mm Depth: 600mm Height: 600mm	Cardboard: Up to 60 kg Plastic: Up to 85 kg	62.3 db (A)	IP 55	Single Phase 230 V, 50 Hz, 10 A					

We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.

Orwak AB Svetsaregatan 4 S-576 33 Sävsjö SWEDEN Tel: +46-(0)382-157 00 info@orwak.com, www.orwak.com

