ORWAK COMPACT 3210-COMBI

ORWAK COMPACT 3210-COMBI is a versatile dual-function unit! With an insert, the baler for cardboard and plastic is quickly transfomed into a drum crusher! Thanks to a small footprint, it fits where space is limited.



Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO_2 emissions. Sorting at source yields a higher quality of waste material for recycling.



COMPACT



Why Orwak Compact?

- Strong compaction on the spot! Requires little space, yet provides effective volume reduction
- + Easy-to-handle light weight bales

ORWAK COMPACT

The Part of the second

The best choice for small to medium size volumes of cardboard and plastic



www.orwakbalers.com

ORWAK COMPACT 3210-COMBI

Baler and drum crusher in the same machine

BALE INDICATOR

A bale indicator alerts you when the machine has reached its capacity.

SMALL FOOTPRINT

It is a compact machine that takes up less than 1 sq. m floor space.

OPTIMAL BALE LOGISTICS

2 bales from model 3210-COMBI fit perfectly on one Euro pallet.



ORWAK COMPACT 3210-COMBI IS OPTIMIZED FOR

PAPER

- + Cardboard
- + Shredded paper
- + Paper sacks

OTHER METALS

+ Steel straps

PLASTIC FOIL+ Shrink film+ Plastic bags

- OTHER PLASTICS
- + Plastic straps

SPECIAL

+ Steel drums

SWITCH BETWEEN LP AND HP

Compacting cardboard or plastic foil? A switch conveniently located on the side of the machine makes it simple to alter the setting from HP for cardboard to LP for plastic foil.

INSERT FOR DRUM CRUSHING

Based on Orwak's standard baler 3210, this model can bale packaging material and when using the insert it becomes an effective drum crusher. It compacts drums 5:1 in 22 seconds. Any liquid residue is collected in the insert. Note! 3210-COMBI is only constructed for metal drums with a thickness of up to 1/32''!




DIMENSIONS									
Α	В	с	D	E	F*				
8'3"	43"	34"	66"	28"	5'10"				
DRUM DIMENSI	ONS		CHAMBER DIN	CHAMBER DIMENSIONS (INTERNAL)					
Max ø 23''	Height max 36''		Height 3'7'', Wid	Height 3'7'', Width: 32'', Depth: 24''					
ENERGY CONSUMPTION									
STANDBY MOD	DE		MAXIMUM OP	MAXIMUM OPERATION ONE HOUR					

2.7 W/H

IAXIMUM OF EXAMON ONE HOL

626 W/H



WEIGHT (MACHINE) TOTAL: 1,642 lbs

TECHNICAL SPECIFICATIONS

LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER				
Width: 31" Height: 19"	22 secs	26,400 lbs.	Width: 32" Depth: 24" Height: 28"	Cardboard: Up to 180 lbs Plastic: Up to 245 lbs	62.4 db (A)	IP 55	3-phase 3x208 V, 60 Hz 3-phase 3x460 V, 60 Hz				

We reserve the right to make changes to specifications without prior notice. Bale weights are dependent upon material type.





Orwak North America, Inc. 9200 Globe Center Drive, Suite 130, Morrisville, NC 27560, USA Phone: +1-800-747-0449, Email: info@orwakbalers.com

DIMENSIONS & SPECIFICATIONS