

MULTIPURPOSE BUCKETS

MP66 | MP72 | MP78 | MP84



JOHN DEERE



Multipurpose Buckets

MP66 | MP72 | MP78 | MP84



Specifications

- Capable of bulldozing, scraping, loading, metering, and clamping material — it's ideal for a wide variety of applications.
- Low-profile geometry allows superior visibility to the cutting edge, increasing efficiency.
- Rugged torque tube equalizes load forces when clamping.
- Heavy-duty design includes tough high-carbon cutting edges, wear-resistant 1055 high-carbon steel at key wear points, and precision cylinders with easy-to-service hardened rods. All pivot points are lubricated with grease fittings.
- To further increase durability and performance, buckets are predrilled for optional bolt-on replaceable cutting edges or toothbars.
- Like all Worksite Pro™ attachments, these multipurpose buckets are optimized to work with John Deere skid steers, compact track loaders, and compact four-wheel-drive loaders. In addition, they're compatible with most competitive models. See your local John Deere skid steer dealer for details.

	MP66	MP72	MP78	MP84
Overall Width	1695 mm (66.75 in.)	1848 mm (72.75 in.)	1981 mm (78.75 in.)	2153 mm (84.75 in.)
Overall Height	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)
Overall Depth	914 mm (36 in.)	914 mm (36 in.)	914 mm (36 in.)	914 mm (36 in.)
Bucket Capacity				
Heaped	0.34 m ³ (12 cu. ft.)	0.38 m ³ (13.1 cu. ft.)	0.40 m ³ (14.2 cu. ft.)	0.43 m ³ (15.4 cu. ft.)
Struck	0.24 m ³ (8.6 cu. ft.)	0.27 m ³ (9.4 cu. ft.)	0.28 m ³ (10.0 cu. ft.)	0.29 m ³ (10.5 cu. ft.)
Empty Weight	394 kg (866 lb.)	417 kg (918 lb.)	452 kg (998 lb.)	468 kg (1,030 lb.)
Cutting Edge Dimensions (1055 high-carbon steel):				
Front Half (front)	19 x 152 mm (0.75 x 6 in.)	19 x 152 mm (0.75 x 6 in.)	19 x 152 mm (0.75 x 6 in.)	19 x 152 mm (0.75 x 6 in.)
Front Half (rear)	19 x 102 mm (0.75 x 4 in.)	19 x 102 mm (0.75 x 4 in.)	19 x 152 mm (0.75 x 6 in.)	19 x 152 mm (0.75 x 6 in.)
Rear Half	12.7 x 152 mm (0.50 x 6 in.)	12.7 x 152 mm (0.50 x 6 in.)	12.7 x 152 mm (0.50 x 6 in.)	12.7 x 152 mm (0.50 x 6 in.)
Cylinders:				
Bore	70 mm (2.75 in.)	70 mm (2.75 in.)	70 mm (2.75 in.)	70 mm (2.75 in.)
Stroke	152 mm (6 in.)	152 mm (6 in.)	152 mm (6 in.)	152 mm (6 in.)
Rod Diameter	38 mm (1.5 in.)	38 mm (1.5 in.)	38 mm (1.5 in.)	38 mm (1.5 in.)
Vehicle Compatibility	318D/E, 319D/E, 320D/E, and 323D/E	318D/E, 319D/E, 320D/E, 323D/E, 326D/E, 328D/E, 329D/E, 332D/E, 333D/E, and 244J	318D/E, 319D/E, 320D/E, 323D/E, 326D/E, 328D/E, 329D/E, 332D/E, 333D/E, and 244J	326D/E, 328D/E, 329D/E, 332D/E, 333D/E, and 244J

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

