

HyPak™



**RAPID CYCLE.
DOUBLE ACTION
COMPACTION.**

STORAGE

COLLECTION

TRANSFER



Flexible Collection



Manual Collection

Using the lowest loading height in the industry for manual collection maximizes operator productivity and safety.



Roll Carts

Cart dumper adds flexibility without the high cost of full automation.



Semi-Automated Hyd-A-Ways

Seamlessly integrates with Hyd-A-Way containers to achieve a highly efficient, low cost operation.

Options Include



- ❖ Onboard 1,500 psi (103 bars) pressure washer keeps on-site equipment clean and sanitized.
- ❖ Frame mounted toolbox available for additional storage space.

Double Action Compaction (DAC™)

The packing blade compacts through the forward-and-return cycle to eliminate wasted strokes.

This innovative design maximizes bucket, hopper and body volume while minimizing cab-to-axle and turning radius.



Unique panel design facilitates material flow during the compaction cycle to achieve higher payloads.

Liquid & powder paint process used on high-wear parts achieves a high gloss durable finish.

Specifications

Approx. Body Weight

9 800 lbs (4 445 kg)

Body Capacity

25 cu yd (19 cu m)

GVWR Recommended

32 000 lbs (14 500 kg)

Cab to Axle

144 inches (3 660 mm)

Hopper Volume

3.7 cu yd (2.8 cu m)

Hopper Loading Height*

36 inches (915 mm)

Packing Force

30 000 ft-lbs (40 675 N-m)

Cycle Time at 1000 RPM

30 seconds

Distributor

Phone: 888-HAUL-ALL (428-5255) Fax: 403.328.9956
403.328.7788

E-mail: sales@haulall.com

www.haulall.com

Haul-All and "Integrating Waste Management" are Registered Trademarks.

