

ARCHITECTURAL



LED Wall Washers

p. 88-89

Up-light or down-light signs, buildings, trees, and displays to highlight and add dimension

LED WALL WASHERS



LED Wall Washers

- High impact illumination fixtures require virtually no maintenance
- Die-cast aluminum alloy housing with enamel finish and tempered glass lens
- Housing and base with built-in driver are fully sealed for use in wet locations (IP65)
- Integrated mounting holes in base/leg brackets and adjustable tilt design maximize on-site flexibility
- Easy to install - multiple RGB arrays can interconnect power (up to 5 units) and data linking (up to 30 units)
- Linear RGB fixtures must be powered directly via their 5ft grounded power cords but allow data linking (up to 30 units)



Specifications: WW RGB Array

Input voltage	120V AC, 60Hz
Color	RGB
Max run	5 units (power), 30 units (data)
Control	RGB
Rating	cETLus, Indoor/outdoor (IP65)
Rated life	100,000 hours



Specifications: LLW White Linear

Input voltage	120V AC, 60Hz
Color	3000K Warm White
Rating	Not rated, Indoor/outdoor (IP65)
Rated life	40,000 hours

Specifications: WW RGB Linear

Input voltage	120V AC, 60Hz
Color	RGB
Max run	30 units (data only)
Control	RGB
Rating	Not rated, Indoor/outdoor (IP65)
Rated life	100,000 hours

WHITE LINEAR



PART NUMBER	COLOR
15.75"L x 2-3/16"W x 5"H • 15W • 700Lm • 25° Beam Angle	
LLW16-WW	3000K WARM WHITE
31.5"L x 2-3/16"W x 5"H • 30W • 1400Lm • 25° Beam Angle	
LLW32-WW	3000K WARM WHITE
47.25"L x 2-3/16"W x 5"H • 45W • 2100Lm • 25° Beam Angle	
LLW48-WW	3000K WARM WHITE



RGB LINEAR*



PART NUMBER	COLOR
47.25"L x 2-3/16"W x 5"H • 45W • 25° Beam Angle	
WW-L48-RGB	RGB

*Includes built in standalone functionality
(can be used without a controller)



RGB ARRAY**



PART NUMBER	COLOR
13"W x 9-1/2"H Array Face x 5-5/8" Dia. Base • 50W	
WW-ARRAY-RGB	RGB

**Requires the use of RGB controller and accessories



RGB ACCESSORIES



DMX-RGB-3

3-Channel Controller

- Nine color presets
- Multiple pre-programmed strobe, dim, and chase functions
- 5ft, 120V AC power cord plus adapter
- Can control up to 30 fixtures
- Signal lead connects to first fixture via data input cable (WW-EC15)



WW36-EX15

RGB Power Extension Cable
15ft length; Interconnect to
create longer lengths
(Use with WW-ARRAY-RGB only)



WW-EC15

RGB Signal Extension Cable
15ft length; Interconnect to
create longer lengths



WW-END

Signal termination end cap
for last fixture in a DMX
controlled series

NOTE: To use WW-L48-RGB or WW-ARRAY-RGB with previous RGB wall washers (LLW-RGB or LW36-RGB Series), item LW-WW-CONVERSION is needed for interconnection of signal cables (sold separately - contact American Lighting).