




EPIQ 4 Downlight

Features

- Excellent color rendering (90+ CRI)
- 2700K / 4000K color temperatures
- Up to 884 lumen output
- Consumes only 9.5 watts
- CLIQ square trims instantly transform the look
- Dimmable with most TRIAC, CL, or ELV dimmers
- Type IC and cETLus Listed for wet locations
- 35,000 hours rated life
- ENERGY STAR certified

Available Finishes



White Dark Bronze

Dimming Options

- TRIAC (5-100%)
- CL (5-100%)*
- ELV (5-100%)*

Listing / Ratings



CLIQ 4 Trim



Technical Information

| | |
|---------------|--|
| Series | E4 |
| Input Voltage | 120V AC, 60Hz |
| CCT | 2700K / 4000K |
| CRI | 90+ |
| Wattage | 9.5W |
| Lumens | Up to 884Lm |
| Beam Angle | 86° |
| Dimmable | 5-100%* |
| Mounting | Recessed mount (requires 4" housing) |
| Rating | cETLus Listed; Type IC; Suitable for wet locations |
| Rated Life | 35,000 hrs |

*Minimum loads may apply

Ordering Information

| | |
|------------------|---------------------------------------|
| E4-B27-WH | 4" White Baffle / 2700K / 817Lm |
| E4-B40-WH | 4" White Baffle / 4000K / 884Lm |
| E4-B27-DB | 4" Dark Bronze Baffle / 2700K / 630Lm |
| E4-27-WH | 4" White Smooth / 2700K / 765Lm |
| E4-27-DB | 4" Dark Bronze Smooth / 2700K / 630Lm |
| Q4-B-WH | 4" Cliq Trim / White Baffle |
| Q4-B-NK | 4" Cliq Trim / Nickel Baffle |
| Q4-B-DB | 4" Cliq Trim / Dark Bronze Baffle |
| Q4-WH | 4" Cliq Trim / White Smooth |
| Q4-NK | 4" Cliq Trim / Nickel Smooth |
| Q4-DB | 4" Cliq Trim / Dark Bronze Smooth |

