

SMALL ANGLE GRINDERS

4-1/2" Slide Switch Grinder

DWE4011



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 7 A (AC/DC) |
| Max Watts Out | 800 MWO |
| Max Horsepower | 1.1 HP |
| No Load Speed | 12,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 3.9 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, and Inner and Outer Flanges |

4-1/2" Paddle Switch Grinder

DWE4120



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 9 A (AC/DC) |
| Max Watts Out | 1140 MWO |
| Max Horsepower | 1.5 HP |
| No Load Speed | 12,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 3.9 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges |

4-1/2" Paddle Switch Grinder (Grounded)

DWE402G



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 11 A (AC/DC) |
| Max Watts Out | 1400 MWO |
| Max Horsepower | 1.8 HP |
| No Load Speed | 11,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 4.6 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges |



4-1/2" Paddle Switch Grinder

DWE402



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 11 A (AC/DC) |
| Max Watts Out | 1400 MWO |
| Max Horsepower | 1.8 HP |
| No Load Speed | 11,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 4.6 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges |



4-1/2" Slide Switch Grinder

DWE4214



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 11 A (AC/DC) |
| Max Watts Out | 1400 MWO |
| Max Horsepower | 1.8 HP |
| No Load Speed | 11,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 4.6 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, and Inner and Outer Flanges |



4-1/2" Paddle Switch Grinder

DWE4012



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 7.5 A (AC/DC) |
| Max Watts Out | 850 MWO |
| Max Horsepower | 1.1 HP |
| No Load Speed | 12,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 3.9 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, and Inner and Outer Flanges |

4-1/2" Paddle Switch Grinder with No Lock-On

DWE4120N



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 9 A (AC/DC) |
| Max Watts Out | 1140 MWO |
| Max Horsepower | 1.5 HP |
| No Load Speed | 12,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | No |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 3.9 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges |

4-1/2" Paddle Switch Grinder Kit

DWE402K



SPECIFICATIONS

| | |
|-------------------------|--|
| Amps | 11 A (AC/DC) |
| Max Watts Out | 1400 MWO |
| Max Horsepower | 1.8 HP |
| No Load Speed | 11,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | Yes |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 4.6 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges, and Kit Box |



4-1/2" Paddle Switch Grinder with No Lock-On

DWE402N



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 11 A (AC/DC) |
| Max Watts Out | 1400 MWO |
| Max Horsepower | 1.8 HP |
| No Load Speed | 11,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | No |
| E-Clutch® System | No |
| Lanyard Ready™ | No |
| Brake | No |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 4.6 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges |



4-1/2" Paddle Switch Grinder with No Lock-On

DWE4222N



SPECIFICATIONS

| | |
|-------------------------|---|
| Amps | 11 A (AC) |
| Max Watts Out | 1400 MWO |
| Max Horsepower | 1.8 HP |
| No Load Speed | 11,000 rpm |
| Spindle Thread | 5/8"-11 |
| Lock-On Switch | No |
| E-Clutch® System | Yes |
| Lanyard Ready™ | Yes |
| Brake | Yes |
| Kickback Brake™ | No |
| Tool Weight (Tool only) | 5.0 lbs |
| Includes | 4-1/2" Type 27 Guard, 2-Position Side Handle, and Inner and Outer Flanges |

