



OVERPACKS IN SMALL, MEDIUM, LARGE, & HUGE!

Whether your need be large or small, we have the pack to fit them all!



POLY-OVERPACK® 20 & 30 SALVAGE DRUMS BIG FEATURES AND BIG SAVINGS!

20 and 30-gallon Salvage Drums are versatile units that can directly contain solids and sludges with security. With a half-turnlid, these ergonomically designed units allow for easy access, unlike competing "hoop-ring designs" that need a bolt and nut. The 20-gallon unit accepts bottles, cans, and 5-gallon pails, while the 30-gallon unit can contain drums w/capacities up to 16 gallons. Units are also nestable, which allows for ease of shipment. Save on shipping cost and storage space!



POLY-OVERPACKS®

Part #	Description	Top Dia. in. (cm)	Bottom Dia. in. (cm)	Ht. in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)	Load Cap. lb. (kg)
1220-YE	20-Gallon	22.25 (57)	18 (46)	19 (48)	10 (4.5)	20 (75.7)	166 (75.3)
1230-YE	30-Gallon*	22.25 (57)	18 (46)	30 (76)	13 (6)	30 (113.5)	220 (100)

Regulations: UN 1H2/X75/S, UN 1H2/Y100/S, *UN 1H2/X100/S, DOT 49 CFR 173.3 (c), EPA, SPCC and NPDES

POLY-OVERPACK® 65 SALVAGE DRUM JUST THE RIGHT SIZE FOR 30-GALLON DRUMS.

Our Poly-Overpack® 65 meets Group 1 packaging standards, Salvage Drum regulations, and is designed to overpack 30-gallon drums. This salvage drum nests for easy storage and has a lid gasket for secure containment. No wasted space! No wasted money!

GREAT AS A SPILL KIT CONTAINER!

It's light enough for one person to handle and large enough to store sufficient absorbent and response equipment for incidental spills.



POLY-OVERPACK® 65

Part #	Top Dia. in. (cm)	Bottom Dia. in. (cm)	Ht. in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)	Load Cap. lb. (kg)
1065-YE	27.75 (70)	23 (58)	37.5 (95)	47 (21)	65 (246.1)	440 (200)

Regulations: UN 1H2/X200/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES

**IF IT'S NOT AN ENPAC SALVAGE DRUM,
IT'S PROBABLY JUST A TRASH CAN.**



YOU SHOULD USE...

OVERPACKS— to provide protection for packages of solids OR for convenience in handling a package or consolidating packages of solids. Not to be used for transportation of hazardous material. **SALVAGE DRUMS**— All mentioned above and for the transport of damaged or leaking drums containing hazardous liquids and hazardous materials.

WHEELED POLY-OVERPACK® SALVAGE DRUMS

ENPAC® Wheeled Poly-Overpacks® are the original mobile one-piece overpack. Completely eliminate the need for a separate dolly to transport the 95-gallon and the 50-gallon polyethylene UN-rated Salvage Drums.

Both have built-in handles and 6" polyolefin wheels that allow for easy steering through doorways and around obstacles. With newly enhanced handles for better gripping and ideal for mobile Spill Kits. (see pg. 43) A Salvage Drum and dolly all in one!

*Tarps available on pages 13 & 48.



WHEELED POLY-OVERPACKS®

Part #	Description	Top Dia. in. (cm)	Bottom Dia. in. (cm)	Ht. in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)	Load Cap. lb. (kg)
1259-YE	50-Gallon	24 (61)	18.5 (47)	45.38 (115)	47 (21)	50 (189.3)	275 (125)
1299-YE	95-Gallon*	31.38 (80)	25.75 (65)	47.5 (121)	56 (25)	95 (359.6)	250 (113)

Regulations: UN 1H2/X125/S, *UN 1H2/X113/S, 49 CFR 173.3, SPCC and NPDES



POLY-OVERPACK® 180T OVERPACK DRUM IDEAL FOR TRANSPORTING AND STORING TRANSFORMERS.

The Poly-Overpack® 180T offers a large 180-gallon capacity to handle the big jobs, while its *Tight Grip* feature ensures a secure seal, saving you time and money.

POLY-OVERPACK® 180T

Part #	Top Dia. in. (cm)	Bottom Dia. in. (cm)	Ht. in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)	Load Cap. lb. (kg)
1180-YE	40.25 (102)	30 (76)	57 (145)	102 (46.3)	180 (681.4)	2,500 (1,134)

Regulations: EPA 40 CFR 761.65, SPCC and NPDES



POLY-OVERPACK® 600 OVERPACK DRUM A HUGE 600-GALLON CAPACITY.

Designed specifically for the storage of large transformers, the Poly-Overpack® 600 offers an easy, cost-effective way to keep larger quantities of hazardous fluids contained.

IT'S HUGE!



POLY-OVERPACK® 600

Part #	Top Dia. in. (cm)	Bottom Dia. in. (cm)	Ht. in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)	Load Cap. lb. (kg)
1051-YE	71 (180)	49.25 (125)	69 (175)	225 (102)	600 (2,271)	5,000 (2,268)

Regulations: EPA 40 CFR 761.65, SPCC and NPDES