

# GET COMPLIANT WITH DEWALT<sup>®</sup>

**OSHA COMPLIANT**  
1926.1153

**220+**  
**SOLUTIONS**  
FOR OSHA TABLE 1 COMPLIANCE

**TOOLS | SHROUDS & ACCESSORIES | DUST EXTRACTORS**

**220+ WAYS**

TO BECOME TABLE 1 OSHA COMPLIANT (1926.1153)

Visit [DEWALT.com/DUST](http://DEWALT.com/DUST) to see all OSHA Compliant Solutions

## DUST EXTRACTION FOR GRINDERS

### 5"-6" High Performance Tuckpointing/Cutting Grinder

DWE46103



#### SPECIFICATIONS

Amps	13 A (AC)
Max Watts Out	1700 MWO
Max Horsepower	2.3 HP
No Load Speed	9000 rpm
Spindle Thread	5/8"-11
Switch Type	Slide with Lock-On
Dust Extraction System	Yes
E-Clutch <sup>®</sup> System	Yes
Lanyard Ready <sup>™</sup>	No
Brake	No
Kickback Brake <sup>™</sup>	No
Max Wheel Diameter	5", 6"
Hose Port Diameter	35 mm Inner / 42 mm Outer
Tool-Free Shroud Change	Yes
AirLock <sup>™</sup> Compatible	Yes
Power Loss Reset	Yes
Tool-Free Flange System	Yes
Tool Weight (Tool only)	8.5 lbs
Includes	2-Position Side Handle, 5"/6" Tuckpoint Shroud, 5" Tuckpoint Diamond Wheel, Inner and Outer Flanges, Hex Key, and Kit Bag

### 5" Surfacing Shroud Kit with Bail Handle

DWE46153



#### SPECIFICATIONS

Amps	11 A (AC)
Max Watts Out	1400 MWO
Max Horsepower	1.8 HP
No Load Speed	11,000 rpm
Spindle Thread	5/8"-11
Switch Type	Slide with Lock-On
Dust Extraction System	Yes
E-Clutch <sup>®</sup> System	No
Lanyard Ready <sup>™</sup>	No
Brake	No
Kickback Brake <sup>™</sup>	No
Max Wheel Diameter	5"
Hose Port Diameter	35 mm Inner / 42 mm Outer
Tool-Free Shroud Change	No
AirLock <sup>™</sup> Compatible	Yes
Tool Weight (Tool only)	6.5 lbs
Power Loss Reset	Yes
Tool-Free Flange System	Yes
Includes	DWE46152 5" Shroud, 5" Diamond Turbo Wheel, Universal Connector, Bail Handle, Side Handle, 5" Type 27 Guard, Hex Key