

## SDS PLUS® ROTARY HAMMERS

### 1-1/8" L-Shape SDS Plus® Rotary Hammer with Dust Collection Kit

D25333KDH



#### SPECIFICATIONS

|                         |  |
|-------------------------|--|
| Amps                    | 8.5 A  |
| Impact Energy           | 3.5 Joules**   |
| No Load Speed           | 0-1000 rpm   |
| Blows / Min             | 0-4480 bpm   |
| Vibration Measurement   | 7.5 m/s <sup>2</sup>   |
| Vibration Control       | Yes, SHOCKS™   |
| Torque Control          | Yes, Integral Clutch   |
| Optimal Drilling Range  | 1/4" - 7/8"  |
| Tool Weight (Tool only) | 8.1 lbs  |
| Service Contract        | 2 Years Free Service   |
| Includes                | DWH304DH OSHA Compliant Dust Extractor, 360° Side Handle, Depth Rod, and Kit Box |

### 1-1/8" L-Shape SDS Plus® Rotary Hammer Kit

D25416K



#### SPECIFICATIONS

|                         |   |
|-------------------------|---|
| Amps                    | 8.5 A                                       |
| Impact Energy           | 4.2 Joules**                                |
| No Load Speed           | 0-820 rpm                                   |
| Blows / Min             | 0-4700 bpm                                  |
| Vibration Measurement   | 8.2 m/s <sup>2</sup>                        |
| Vibration Control       | Yes, SHOCKS™                                |
| Torque Control          | Yes, E-Clutch® and Integral Clutch          |
| Optimal Drilling Range  | 1/2" - 7/8"                                 |
| Tool Weight (Tool only) | 9.2 lbs                                     |
| Service Contract        | 2 Years Free Service                        |
| Includes                | 360° Side Handle with Depth Rod and Kit Box |



## SDS MAX COMBINATION HAMMERS

### 1-9/16" SDS Max Combination Hammer Kit

D25481K



#### SPECIFICATIONS

|                         |                              |
|-------------------------|------------------------------|
| Amps                    | 10.5 A                       |
| Impact Energy           | 6.1 Joules**                 |
| No Load Speed           | 0-540 rpm                    |
| Blows / Min             | 0-3150 bpm                   |
| Vibration Measurement   | 9.4 m/s <sup>2</sup>         |
| Vibration Control       | Yes, SHOCKS™                 |
| Torque Control          | Yes, Integral Clutch         |
| Optimal Drilling Range  | 1/2" - 1-1/8"                |
| Tool Weight (Tool only) | 13.0 lbs                     |
| Service Contract        | 2 Years Free Service         |
| Includes                | 360° Side Handle and Kit Box |

### 1-3/4" SDS Max Combination Hammer Kit

D25604K



#### SPECIFICATIONS

|                         |                                    |
|-------------------------|------------------------------------|
| Amps                    | 13.5 A                             |
| Impact Energy           | 8.0 Joules**                       |
| No Load Speed           | 210-415 rpm                        |
| Blows / Min             | 1430-2840 bpm                      |
| Vibration Measurement   | 9.1 m/s <sup>2</sup>               |
| Vibration Control       | Yes, SHOCKS™                       |
| Torque Control          | Yes, E-Clutch® and Integral Clutch |
| Optimal Drilling Range  | 5/8" - 1-1/4"                      |
| Tool Weight (Tool only) | 15.1 lbs                           |
| Service Contract        | 2 Years Free Service               |
| Includes                | 360° Side Handle and Kit Box       |

### 1-7/8" SDS Max Combination Hammer Kit

D25733K



#### SPECIFICATIONS

|                         |                                    |
|-------------------------|------------------------------------|
| Amps                    | 15 A                               |
| Impact Energy           | 13.3 Joules**                      |
| No Load Speed           | 177-355 rpm                        |
| Blows / Min             | 1352-2705 bpm                      |
| Vibration Measurement   | 9.6 m/s <sup>2</sup>               |
| Vibration Control       | Yes, SHOCKS™                       |
| Torque Control          | Yes, E-Clutch® and Integral Clutch |
| Optimal Drilling Range  | 3/4" - 1-3/4"                      |
| Tool Connect Tag Ready™ | Yes                                |
| Tool Weight (Tool only) | 15.0 lbs                           |
| Service Contract        | 2 Years Free Service               |
| Includes                | 360° Side Handle and Kit Box       |

### 2" SDS Max Combination Hammer Kit

D25773K



#### SPECIFICATIONS

|                         |                              |
|-------------------------|------------------------------|
| Amps                    | 15 A                         |
| Impact Energy           | 19.4 Joules**                |
| No Load Speed           | 145-290 rpm                  |
| Blows / Min             | 1105-2210 bpm                |
| Vibration Measurement   | 12.4 m/s <sup>2</sup>        |
| Vibration Control       | Yes, SHOCKS™                 |
| Torque Control          | Yes, Integral Clutch         |
| Optimal Drilling Range  | 7/8" - 1-7/8"                |
| Tool Weight (Tool only) | 16.0 lbs                     |
| Service Contract        | 2 Years Free Service         |
| Includes                | 360° Side Handle and Kit Box |