

60V MAX* FLEXVOLT® COMBINATION HAMMERS & DUST EXTRACTION

2" SDS MAX Combination Hammer

DCH773Y2



SPECIFICATIONS

| | |
|-------------------------|---|
| Voltage | 60V MAX* |
| Impact Energy** | 19.4 Joules |
| No Load Speed | 145 - 290 RPM |
| Blows/Min | 1,105 - 2,210 BPM |
| Vibration Measurement | 10.0 m/s ² |
| Vibration Control | Yes, SHOCKS™ |
| Torque Control | Yes, E-Clutch® System and Integral Clutch |
| Optimal Drilling Range | 7/8" - 1-7/8" |
| Tool Weight (Tool only) | 21.0 lbs |
| Service Contract | 2 Years Free Service |
| Includes | 360° Side Handle |

AVAILABLE

| | |
|----------|--|
| DCH773Y2 | Also Includes: (2) 20V/60V MAX* FLEXVOLT® Lithium Ion Batteries (12.0 Ah), Fast Charger, and Kit Box |
|----------|--|



DCH773Y2

FLEXVOLT® 60V MAX* DUST EXTRACTOR

DCV585B



SPECIFICATIONS

| | |
|---------------------------|---|
| AIR LOCK | Yes |
| Automatic Filter Cleaning | Yes |
| HEPA Filter | Yes |
| OSHA Compliance | Table 1† |
| CFM | 125 |
| Wireless Tool Control | Yes |
| Tank Capacity | 2 Gallon |
| Tool Weight | 17.6 lb |
| Includes | 8' long Anti-Static hose, HEPA Filters, Wireless Tool Control Remote, Fleece Filter Bag |

AVAILABLE

| | |
|----------|---|
| DCV585B | Batteries and Charger Sold Separately |
| DCV585T2 | Also Includes: (2) 20V/60V MAX* FLEXVOLT® Lithium Ion |



DCV585T2

60V MAX* FLEXVOLT® STUD & JOIST DRILLS

Brushless Stud and Joist Drill with E-Clutch® System

DCD460B



SPECIFICATIONS

| | |
|-----------------------------|--|
| Voltage | 60V MAX* |
| Max Power | 1540 MWO |
| Chuck Size | 1/2" |
| Chuck Type | Metal, Keyed |
| # of Speed Settings | 2 |
| No Load Speed | 0-300/0-1250 rpm |
| Self Feed Capacity in Wood | 4-5/8" |
| Hole Saw Capacity in Wood | 6-1/4" |
| Auger Bit Capacity in Wood | 1-1/2" |
| Twist Bit Capacity in Steel | 1/2" |
| Hole Saw Capacity in Steel | 5" |
| Clutch | Mechanical, E-Clutch® System |
| Tool Weight (Tool only) | 10.6 lbs |
| Includes | 2-Position Side Handle, Bail Handle, and Chuck Key |

AVAILABLE

| | |
|----------|--|
| DCD460B | Batteries and Charger Sold Separately |
| DCD460T1 | Also Includes: (1) 20V/60V MAX* FLEXVOLT® Lithium Ion Battery (6.0 Ah), Charger, and Kit Bag |
| DCD460T2 | Also Includes: (2) 20V/60V MAX* FLEXVOLT® Lithium Ion Batteries (6.0 Ah), Charger, and Kit Bag |



DCD460T1



DCD460T2

Brushless In-Line Stud and Joist Drill with E-Clutch® System

DCD470B



SPECIFICATIONS

| | |
|-------------------------------|---------------------------------------|
| Voltage | 60V MAX* |
| Max Power | 2600 MWO (3.5 max HP) |
| Chuck Size | 1/2" |
| Chuck Type | Metal, Keyed |
| # of Speed Settings | 2 |
| No Load Speed | 0-400/0-1320 rpm |
| Self Feed Capacity in Wood | 4-5/8" |
| Hole Saw Capacity in Wood | 6-1/4" |
| Auger Bit Capacity in Wood | 2" |
| Twist Bit Capacity in Steel | 1/2" |
| Diamond dry core bit in Block | 6" |
| Diamond dry core bit in Brick | 5" |
| Clutch | Mechanical, E-Clutch® System |
| Tool Weight (Tool only) | 14.4 lbs |
| Includes | 2-Position Side Handle, and Chuck Key |

AVAILABLE

| | |
|----------|--|
| DCD470B | Batteries and Charger Sold Separately |
| DCD470X1 | Also Includes: (1) 20V/60V MAX* FLEXVOLT® Lithium Ion Battery DCB609 (9.0 Ah), DCB115 Charger, and Kit Bag |



DCD470X1