

20V MAX* CHARGERS

Simultaneous Four-Port Fast Charger

DCB104



SPECIFICATIONS

| | |
|-------------------------|----------------------------------|
| Compatibility | 12V MAX*, 20V MAX*, 20V/60V MAX* |
| Output Current | 8 Amps per Port (4 Ports) |
| Wall Mountable | Yes |
| Handle | Yes |
| Tool Connect Tag Ready™ | Yes |
| TOUGHSYSTEM® Compatible | Yes |
| USB Outlets | No |
| Fan Cooled | No |

1800 Watt Portable Power Station™ and Simultaneous Charger

DCB1800B



SPECIFICATIONS

| | |
|-----------------|---|
| Output | 120V MAX* |
| Compatibility | 20V MAX* Lithium Ion Batteries and 20V/60V MAX* FLEXVOLT® Lithium Ion Batteries |
| Max AC Output | 3600 Watts Peak |
| Rated AC Output | 1800 Watts Continuous |
| Power Source | Extension cord, and batteries sold separately. |

12V-20V/60V MAX* Dual Port Charger

DCB102



SPECIFICATIONS

| | |
|-------------------------|----------------------------------|
| Compatibility | 12V MAX*, 20V MAX*, 20V/60V MAX* |
| Output Current | 4 Amps per Port |
| Wall Mountable | No |
| Handle | No |
| Tool Connect Tag Ready™ | No |
| USB Outlets | Yes |
| Fan Cooled | No |

12V-20V/60V MAX* Vehicle Charger

DCB119



SPECIFICATIONS

| | |
|-------------------------|----------------------------------|
| Compatibility | 12V MAX*, 20V MAX*, 20V/60V MAX* |
| Output Current | 4 Amps |
| Wall Mountable | No |
| Handle | No |
| Tool Connect Tag Ready™ | No |
| USB Outlets | No |
| Fan Cooled | No |

12V-20V-60V MAX* Charger

DCB115



SPECIFICATIONS

| | |
|-------------------------|----------------------------------|
| Compatibility | 12V MAX*, 20V MAX*, 20V/60V MAX* |
| Output Current | 4 Amps |
| Wall Mountable | Yes |
| Handle | No |
| Tool Connect Tag Ready™ | No |
| USB Outlets | No |
| Fan Cooled | No |

20V MAX* Fast Charger

DCB118



SPECIFICATIONS

| | |
|-------------------------|----------------------------------|
| Compatibility | 12V MAX*, 20V MAX*, 20V/60V MAX* |
| Output Current | 4 Amps |
| Wall Mountable | Yes |
| Handle | No |
| Tool Connect Tag Ready™ | No |
| USB Outlets | No |
| Fan Cooled | Yes |

20V MAX* BATTERY ACCESSORIES

USB Power Source

DCB090



SPECIFICATIONS

| | |
|---------------------------|----------------------------------|
| Voltage | 12V MAX*, 20V MAX*, 20V/60V MAX* |
| USB Ports | 2 |
| State of Charge Indicator | Yes |
| Tool Weight (Tool only) | 0.5 lbs |

18V to 20V MAX* Adapter

DCA1820



SPECIFICATIONS

| | |
|------------------|--|
| Voltage | 18V to 20V MAX* |
| Not For Use With | DEWALT 18V Nailers, DEWALT Charger / Radios, DCS370 Band Saw |

Accepts DEWALT FLEXVOLT® Batteries

PORTABLE POWER WHEN YOU NEED IT

NO GAS NEEDED TO RUN

POWER WITH (4) 20V MAX* BATTERIES,
OR CHARGE WITH CORD

**CORDED OR
CORDLESS**

3600

Peak Watts Out

From (4) 20V MAX* Batteries

AVAILABLE

| | |
|----------|--|
| DCA1820 | Battery Adapter Only. |
| DCA2203C | Also Includes: (2) 20V MAX* Lithium Ion Batteries (2.0 Ah) and Charger |



DCA2203C