



STEEL SPILL DECKS™ LOW PROFILE FLAMMABLE STORAGE

Our economical and compliant 5" Steel Spill Decks™ offer containment solutions for general house-keeping and maintenance in storage and dispensing areas. Constructed of heavy gauge and corrosion resistant galvanized steel, these decks can be grouped and joined together with the included binders and anchors to form leak-free dispensing stations.



- Optional ramps for ease of handling on and off deck surfaces.
- 100% inspected welds for leaktightness
- Relocatable
- Expandable
- Easy install & clean up
- Joint binders and anchors available upon request



STEEL SPILL DECKS™

Part #	Description	Dimensions L x W x H in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)	Load Cap. psf
9645-GS	4' x 5'	49 x 61 x 5 (124 x 155 x 13)	432 (196)	66 (249)	350
9646-GS	4' x 6'	49 x 73 x 5 (124 x 185 x 13)	501 (227)	74 (280)	350
9655-GS	5' x 5'	61 x 61 x 5 (155 x 155 x 13)	513 (232.7)	77 (291.5)	350
9656-GS	5' x 6'	61 x 73 x 5 (155 x 185 x 13)	595 (270)	93 (352)	350

SPILL DECK RAMPS

Available in lengths matching Spill Deck dimensions, these solid steel ramps allow for effortless material handling on and off decks.



SPILL DECK RAMP

Part #	Description	Dimensions L x W x H in. (cm)	Weight lb. (kg)
9640-GS	4' Ramp	48 x 25 x 5 (122 x 64 x 13)	67 (30.4)
9650-GS	5' Ramp	60 x 25 x 5 (152 x 64 x 13)	83 (37.6)
9660-GS	6' Ramp	72 x 25 x 5 (183 x 64 x 13)	109 (49.4)

SEE PG 76
FOR CHEMICAL
COMPATIBILITY
GUIDE



SINGLE CYLINDER DOLLY™ HD



Just as durable and half the size. The Single Cylinder Dolly™ HD is designed for demanding industrial facilities or tough outdoor applications in which transport of a single cylinder is required. Accommodates one cylinder, up to 15" in diameter, including class 300 SCF industrial gas cylinders and No. 5 acetylene cylinders. Rugged, solid wheels standard on Part # 7301-BK-A to maximize maneuverability over rough terrain.

DUAL CYLINDER DOLLY™ EASIER CYLINDER LOADING, BETTER MANEUVERABILITY, AND LARGE TRAY FOR TOOLS.

The Dual Cylinder Dolly™ is designed to be a more functional, maneuverable, and better balanced transporter for gas cylinders than conventional dollies or forklifts. Ideal for industrial or construction operations, the Dual Cylinder Dolly™ can accommodate a variation of two cylinders including class 300 SCF industrial gas cylinders and No. 5 acetylene cylinders. Specifically designed for joint movement of multi-sized cylinders with featured 10" and 13" compartments to guarantee your cylinder's perfect fit!

The dolly's lightweight yet durable polyethylene construction and effective counter balancing makes it easy to handle with minimum physical effort. Tough 16.5" diameter pneumatic wheels offer the best maneuverability over any terrain.

Unlike metal cylinder carts, the Dual Cylinder Dolly™ is spark-resistant and the rugged polyethylene construction will not rust or corrode under harsh weather conditions.

*Can fit up to (1) 13" & (1) 11" cylinder.



20.5" built-in tray holds tools, valves and torches.

CYLINDER DOLLY™

Part #	Description	Dimensions L x W x H in. (cm)	Weight lb. (kg)	Load Cap. lb. (kg)
7301-BK	Single HD	23.75 x 23 x 46 (60 x 58 x 117)	28 (12.7)	250 (113.4)
7301-BK-A	Single HD ATD	23.75 x 23 x 46 (60 x 58 x 117)	35 (15.9)	250 (113.4)
7302-BK	Dual	37 x 23.5 x 45 (94 x 60 x 114)	56.9 (25.8)	500 (227)


Regulations: OSHA 29 CFR 1910.253

UNIVERSAL CYLINDER BRACKET™

Ideal for low-cost wall or truck mounted storage. Design your own configuration to hold one, two, three, or x amount of cylinders with extendable modular flexibility. Units link together to customize the amount of cylinders needed. Attaches to any wall or truck bed securely and easily. Accommodates cylinders from 3" to 10" in diameter and saves space on any wall. Straps included.



ENHANCED
DESIGN



CYLINDER BRACKET™

Part #	Description	Dimensions L x W x H in. (cm)	Weight lb. (kg)
7216-YE	Universal Cylinder Bracket	15.3 x 6.3 x 3.3 (38.7 x 15.9 x 8.3)	1 (.5)

Regulations: OSHA 29 CFR.1910