

# Brass StreamMaster Monitors

StreamMaster Monitors have a uniquely designed, low profile 4" waterway with cast-in turning vanes. When coupled with an 80 psi nozzle, the pump can operate at lower pressures for flows up to 2000 gpm (7600 lpm).

### 3572 Brass StreamMaster Electric Monitor

A compact heavy duty, brass, 1000 GPM (4000 LPM) electric monitor designed for harsh environments.

- Heavy duty brass construction
- 12 or 24 volt DC (24 volt CE approved) for non hazardous locations - Must specify
- 348° of horizontal and 135° of vertical travel both with adjustable stops
- Manual override



STYLE 3572 Electric Brass StreamMaster shown with STYLE 4471 AkroFom Master Stream Nozzle

### 3571 Brass StreamMaster Manual Monitor

The Streammaster Manual Monitor is a dual handwheel controlled monitor suited for large flow needs in fixed site installations.

- Heavy duty brass construction
- Full 360° horizontal travel and 135° vertical travel, both with adjustable stops
- Elevation 45° below to 90° above horizontal



STYLE 3571 Brass StreamMaster shown with STYLE 5171 Master Stream Nozzle

Style	Weight lbs. (kg)	Height	Width	Inlet	Outlet	Flow	
						GPM	LPM
3572	33 (15 kg)	16 5/8" (422 mm)	14 1/4" (362 mm)	4" FL (100 mm)	3 1/2" NH (89 mm)	1000	4000
3571	45 (20.5 kg)	16 5/8" (422 mm)	14 1/4" (362 mm)	4" FL (100 mm)	3 1/2" NH (89 mm)	2000	7600