

## 20V MAX\* GRINDERS

**XR® Brushless 4-1/2" Angle Grinder**  
DCG413B



### SPECIFICATIONS

Voltage	20V MAX*
No Load Speed	9000 rpm
Spindle Lock	Yes
Spindle Thread	5/8" - 11
E-Clutch® System	Yes
Kickback Brake™	Yes
Tool Weight (Tool only)	3.7 lbs
Includes	4-1/2" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges, and Hex Wrench

### AVAILABLE

<b>DCG413B</b>	Batteries and Charger Sold Separately
<b>DCG413R2</b>	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (6.0 Ah), Charger, and Kit Bag



DCG413R2

**XR® Brushless 4-1/2" / 5" Flathead Angle Grinder**  
DCG413FB



### SPECIFICATIONS

Voltage	20V MAX*
No Load Speed	9000 rpm
Spindle Lock	Yes
Spindle Thread	5/8" - 11
E-Clutch® System	Yes
Kickback Brake™	Yes
Tool Weight (Tool only)	3.9 lbs
Includes	5" Type 27 Guard, 2-Position Side Handle, Inner and Outer Flanges, and Hex Wrench

### AVAILABLE

<b>DCG413FB</b>	Batteries and Charger Sold Separately
<b>DCG413FR2</b>	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (6.0 Ah), Charger, and Kit Bag



DCG413FR2

**4-1/2" / 5" Angle Grinder**  
DCG412B



### SPECIFICATIONS

Voltage	20V MAX*
No Load Speed	8000 rpm
Spindle Lock	Yes
Spindle Thread	5/8" - 11
Tool Weight (Tool only)	4.1 lbs
Includes	5" Type 27 Guard, Hex Wrench, and 2-Position Side Handle

### AVAILABLE

<b>DCG412B</b>	Batteries and Charger Sold Separately
<b>DCG412P2</b>	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (5.0 Ah), Charger, and Kit Bag



DCG412P2

**XR® Brushless Variable Speed Die Grinder**  
DCG426B



### SPECIFICATIONS

Voltage	20V MAX*
No Load Speed	0-25,000 rpm
Spindle Lock	No
Spindle Thread	1/4" Collet
Tool Weight (Tool only)	3.9 lbs
Includes	(2) Wrenches and 1/4" Collet

### AVAILABLE

<b>DCG426B</b>	Batteries and Charger Sold Separately
<b>DCG426M2</b>	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (4.0 Ah), Charger, and Kit Bag



DCG426M2

## DUST EXTRACTION FOR GRINDERS

**5" / 6" Cutting/Tuckpointing Shroud**  
DWE46100



### SPECIFICATIONS

Max Wheel Diameter	5" / 6"
Hose Port Inner Diameter	35 mm
Hose Port Outer Diameter	42 mm
Tool-Free Shroud Change	No
AirLock™ Compatible	Yes

**5" Surface Grinding Dust Shroud**  
DWE46152



### SPECIFICATIONS

Max Wheel Diameter	5"
Hose Port Inner Diameter	35 mm
Hose Port Outer Diameter	42 mm
Tool-Free Shroud Change	No
AirLock™ Compatible	Yes